#### No. IV-21011/7/2010-Prov-I Government of India Ministry of Home Affairs

26, Man Singh Road, Jaisalmer House, New Delhi, 1.7.2010

To The DGs: Assam Rifles/BSF/CISF/CRPF/ITBP/NSG/SSB/BPR&D

Subject: - Specifications of various Medical/Hospital Equipments -regarding

Sir,

The Specifications for the following Medical/Hospital Equipments have been accepted and approved by the Competent Authority in MHA and the same are enclosed for information and Record:-

- Glycosylated Hb Automatic Reader-Annex-A
   Infant Open Care System-Annex-B
- 3) Refraction Unit-Annex-C
- 4) Auto Refractor-Annex-D
- 5) Embalming Machine-Annex-E
- 6) Oxygen Concentrator-Annex-F
  7) Automated S. Electrolyte Reader-Annex-G
- 8) Dental Chair-Annex-H
- 9) Anaesthesia Work Station-Annex-I

Henceforth, all the CPMFs should procure the above items required by them strictly as per the laid down Specifications.

Under Secretary to the Govt. of India

Encis: as above

Copy to:-

DD(Procurement),MHA

Copy for information to:-

PS to JS(PM),MHA

#### TECHNICAL SPECIFICATIONS OF DENTAL CHALL

#### GENERAL DESCRIPTION:

- Chair mount Dental Unit complete with all respects which should swivel Left to Right and vice-versa for Left or Right handed Dentist.
- Should be full physiologic body contoured, completely motorized hydraulically driven Chair with absolute smooth non jerky, soft start and soft- stop movements.
- dental chair should be programmable with at least Four programmes of which two programmes for patient entry, one for rinse and one for patient exit, for two dentists A&B. One of the four programmes should be to set head low position in case of medical emergencies. Chair should have synchronised movement that when head rest goes down in supine or head low position the foot end of the chair board should raise. The chair should be programmable with a touch of a button.
- Chair should have possibilities of swivel left and right from base unit more than  $30^{\rm o}$
- Arm-rests should be multi-functional & easily adjustable, with at least one arm which rotates out of way to streamline patient entry/exit.
- Multi-purpose, adjustable head-rest for comfortable support of head, which should also be adjustable for pediatric & handleapped patients for exact adaption to the back of the head
- Touch pad control system should be multi-functional for Chair and Unit Master on/off. Halogen light on/off, with variable intensity, Bowl Flush, Tumbler fill , full chair function manual and programmable positioning.
- It should have functions for light cure unit, intra oral camera, micro motor with endo function. All in built.
- In built Anti-retraction valves and flush valve system for infection control
- Multifunction, easy to use foot-switch. It should provide all chair movements, adjustable and programmable position
- Integrated 17 inches LCD/TFT monitor should be provided for RVG (brand should be mentioned)

#### Operating Light

 Should have an optically designed multi surface glass reflector having three intensity controls and with sensing device and shadow less.

Becaul-

W. M



- Light Head should have three axial movements i.e Horizontal, Vortical and Axial diagonal adjustment at least 30 degree tilt on either side.
- Should be quartz halogen Xenon bulb with spare bulb and holder located at Light Head area for quick maintenance.
- Should have feathered- edge, balanced intensity light pattern
- Should have three position intensity switch with high medium and

#### Suction and Syringes

- Should have high and low volume motorized Suction system should have high and low volume motorized suction system with separating tank and automatic self-cleaning separating tank to allow continuous draining and equipped with fine particles collector and amalgam separators...
- Should have swivel Vitreous China Bowl with adjustable cup fill
- Should have clean water bottle system
- Should have autoclavable Saliva ejectors, autoclavable high
- Volume evacuator and autoclavable six way syringe.

## Ceramic Spittoon and Tumbler with water connection and auto start

#### Foot control:

Multifunctional, easy-to-use foot control. It should provide all chair movements, adjustable and programmable position

## Dental working stool for dentist as well as for assistant:

- Should have cast-aluminium base with 5 -castors
- Should have adjustable lumbar support
- Integral hydraulic system for height adjustment

#### Modular Overhead delivery system with Delivery System) on Pheumatic brake arm with whipdown arms (Continental

- Two terminals of fiber-optic head air rotor hand pieces
- One short head and one stand head air rotor hand pieces with spray and non-retraction valve.
- One micro motor (40,000 RPM) with fiberoptic straight and contra hand pieces and one endo hand piece.
- Ultrasonic endo dontic hand piece: Ultrasonic endo dontic tips and files. One complete set of
- All hand-piece tubing should be of vinyl material.
- Unit block should be of pneumatic.
- No solenoid or kink valves.

 All water line tubings should be made of ALPHASUN material. Tubing should have silver particle ionisation to protect water

## The following accessories will part of the equipment to be supplied.

## Light curing unit LED-based with protective shield

- It should be attached with chalr unit
- Noise less & without fan
- Should be able to cure to a depth of 3-6 mm
- Should have microprocessor with three modes: fast, pulse and ramping. Should be without infra-red
- Light intensity should be able to generate optical power up to • Wavelength range420-480nm

#### Piezo electric scaler:

- it should also be provided in overhead delivery module.
- It should have automatic protection control for maximum safety
- Ultra-sound frequency ranging from at least 27,000-33,000 Hz
- Should be provided with frequency tuning.
- Should have an intelligent control system of amplitude according to the resistance encountered by the tip and the setting mode

#### Instrument table:

- Stainless Steel removable instrument trays (quantity 2 nos.). Must have swing-arm with wide swivel
- Size not less than 20'x 8'
- With height adjustment and locking facility

#### Oil free compressor:

- It should be compact and silent with internal anti-corrosive
- It should be One cylinder made up of cast iron ,oil free with
- It should have tank capacity of at least 20 litres
- it should have auto cut-off switch
- Pressure range: 5.5 8.0 bar
- Should have suction capacity of 100 to 120 litres per minute at

X-ray viewer: for viewing IDPA x-ray must be in-built with the unit

RVG unit including intra-oral X-ray machine, computer, USB cam (high resolution digital Intra-oral camera):

#### Atra-oral X-ray machine, micro-processor controlled, Tube current: 70 kv

- Focal spot: 0.8 mm.
- Focus to skin distance: standard 20 cm
- Outy cycle: At least 1:32, i.e. waiting time between two exposures for cooling of X-ray tute (10-20 sec at least)
- Timer settings: Child/adult selection, upper &lower selection, also Bitewing & occlusion function †aw
- Exposure times: range from 0.02 to 3.2 sec at least
- Low-bose setting for digital receptor
- Facility of remote operation should be provided.
- Automatic correction facility for mains fluctuations
- Hand switch timer with at least 3 mtr coiled cord Hygienic touch-buttons
- Radiation safety apron should be provided
- Double pantographic arm with vertical & horizontal movements, floor mount, mobile on castors,
- The system should comply with national quality certification /international standards for radiation safety including

# Digital intra-oral camera should have following specification

- Should be portable, light weight, convenient and user friendly should be card free & should have D3B cable connectivity
- Should have focus free optics & fog free

### R V G SENSOR & SOFTWARE

- Theoretical resolution: more than 25 lines per mm.
- Actual true resolution: more than 20 lines per mm
- Gray shades that can be resolved: 4000 minimum
- Number of pixels in sensor: 1.8 pixel minimum
- The product should be totally mobile and connected to PC through
- Sensor should have smooth surfaces with rounded corners & edges
- Should have image sharpness filters
- It should have interface features like direct integration with other devices like intra-oral camera, panoramic systems,
- Conversion/upgradation of the software should be available
- Length of sensor wire should be minimum 2 metres
- Sensor should be provided with software facility to enhance zoom, colorize, invert & rotate the image. Sensor life >400,000 exposures
- Should have auto take feature - no need to reset between exposure
- Should be DICOM compatable, user-friendly and powerful program that acquires processes and archives images.

- Should have caries detection software.
- Should be supplied with sensor holder.
- COMPUTER with latest configuration (256 GB H)D, 2 GB RAM, Intel core2 duo processor >2.5 GHz, with windows 7 OS).
- 17'' TFT screens (one mounted on chair and other on desk) & colour printer with appropriate cabinet for computer and printer (Make/model of the computer/ peripherals should be mentioned)

#### Endodontic micro motor with built in spex locator:

- · Riectronically controlled, endodontic micro-motor with built in apex locator
- should start automatically once file enters the canal & stop automatically once it reaches preset position near apex
- Should stop &reverse if the file clogs in canal
- Should negotiate curved canals
- Should have high, low & manual speed modes with auto-torque
- Autoclavable hand piece, mini contra-head for easy access &viewing

#### Glass bead sterilizer (ISI certified) for disinfecting endodontic files with appropriate ratings

## Digital -Electronically Controlled steamfast AUTOCIAVE Table top type

- Micro-processor controlled electronics
- Patented steam generation system
- Capacity 16-20 litres at least
- Customized vacuum drying
- Wide range of sterilization programmes
- Also should have an option of emergency sterilization program of at least 10 minutes lesser than this is desirable.
- Integrated water filling & draining tanks
- Flectronic-controlled locking system for additional safety

High quality, IS( certified, with appropriate ratings for above Stabilizer: operatory

#### HAND PIECE STERILISER

system with automatic 35 seconds UV hand piece steriliser maintenance programme for cleaning and Jubrication of all types of hand pieces

### Dental Ultrasonic cleaning Unit Bench Top

- water resistant Bench Top cleaner with electronic times construction, stainless steel tank, with 2 to 3 litres capacity
- one Sterile UV light storage cabinet for autoclaved instruments Instrument cabinets -

one dental instrument stackable cabinet having wash basin, top made of artificial marble/grapite, durable, easy to clean with at least 3-4 separate drawer compartments, with inner power supply socket to use small equipments.

One mobile stackable cabinet should also be provided.

## System configuration accessories, spares and consumables:

- All consumables for installation /standardization of the system
- Complete installation of the system including water input and drainage has to be installed

Standards and safety:

The accessories of the dental unit should carry appropriate certifications like FDA/CK/BIS/ISO/ IEC/ISI, whichever applicable. Make & model of all accessories/attachments should be specified

#### Documentation:

- Certificate of calibration and inspection
- User /technical/maintenance manuals to be supplied
- List of accessories with their number and costing

Log Book with instructions for maintenance purpose.

DR.N.k.Bhambri IG (Medica) PO

Dr. Sandhya Thapliyal Specialist MO/DC,ITBP MEMBER-III

Dr. Brijesh Kumar 2IC (Medical) SSB MEMBER-I

The dry Dr. Jitendra KumarSahu MO CRPF MEMBER-IV

Dr Amit Butola CMO BSF МЕМВЕК-Ц

AC DENTIST, ITBP CO-OPTED MEMBER

TECH. APPROVED

DR. R.S Rathore ADG (MEDIÇAL)