

रक्षा मंत्रालय MINISTRY OF DEFENCE संयुक्त सेवा स्पेसिफिकेशन JOINT SERVICES SPECIFICATION

ON

Gloves, leather, while, Lined

JSS: 8415-09: 2000 (Revisión No. 2)

मानकीकरण निदेशालय रक्षा उत्पादन विभाग रक्षा मंत्रालय, 'एच' ब्लॉक, निर्माण भवन-डाकघर नई दिल्ली - 110 011

DIRECTORATE OF STANDARDISATION DEPARTMENT OF DEFENCE PRODUCTION MINISTRY OF DEFENCE, 'H' BLOCK, NIRMAN BHAVAN P.O, **NEW DELHI - 110 011**

JSS 8415-09:2000 Directorate of Sanda (Revision No.2) car availar, of Par-

RAKSHA MANTRALAYA MINISTRY OF DEFENCE

JOINT SERVICES SPECIFICATION

ON

GLOVES, LEATHER, WHITE, LINED

(DS Cat No. 841,5-000 176 to 000 178)

MANAKIKARAN NIDESHALAYA RAKSHA UTPADAN AVAM POORTI VIBHAG RAKSHA MANTRALAYA `H' BLOCK, DHQ PO NEW DELHI - 110 011

DIRECTORATE OF STANDARDISATION
DEPARTMENT OF DEFENCE PRODUCTION AND SUPPLIES
MINISTRY OF DEFENCE
'H' BLOCK, DHO PO
NEW DELHI - 110 011

JSS 8415-09:2000 (Revision No.2)

LIST OF MEMBERS ASSOCIATED WITH THE REVISION OF THIS STANDARD

The revision of Joint Services Specification has been approved by Air Cmde SM Taxali, Chairman, Stores Standardisation Sub Committee by circulation .

2. The following members have been associated in approving the draft:-

Sl. No.	Name and Designation		Organisation
1	Gp Capt A. Chaudhuri, VSM	-	JDQAS(Aero)/ Air HQ DQA(S)
2 3 4	Lt Col SD Fandey, Deputy Director Sh J.C. Makani, PScO, Deputy Controller Lt Col A.S Bajwa, Deputy Controller	-	
4 5 6 7	Sh A.A. Khan, PScO, Deputy Controller Sh Devki Nandan, SSO I, Asstt, Controll Sh S.V. Mehrotra, STA Sh M.C. Sharma, Asstt, Director	er- - -	CQA(PP) DQA(N) DGAQA
8 9 10 11	Sh Pankaj Chawla Lt Col GS Waraich, Ord.Dte (CP Cell) Subedar S.K. Biswas, Stdn, Cell (Army)	-	1170 De / 1 170
12	Wg Cdr Chaturvedi, Deputy Director	-	Air HQ NHQ/DNA
14 15 16	Sh V.P.S. Chawla, NSO Deputy Director Lt A Rana, Asstt Director Sh S.K. Kureel, Sc 'D'	-	NHQ/DOS(E) DMSRDE DMSRDE
17 18	Sh Balak Ram, TO(B) Sh B.S.Narula, Sc'C'Secretary		SSSC

JSS 8415-09:2000 mectorate of Standard (Revision No.2) Directorate of Standard of Date of No.2

RECORD OF AMENDMENTS

Amendment :		Authority Amended by	Signature
No Date	pertains to:	Name & Appointmen	t! &
1 1	Srl No./Para No./	! (IN BLOCK LETTERS	
1 1	Column No.		, Dace

JSS 8415-09:2000 titerorate of Standard (Revision No.2)

CONTENTS

					Pag	9.0	No	1-
ο.	FOREWORD			(6 ¹⁾	•		: 1	
1.	SCOPE		5.	22			2	
2.	RELATED SPECIFICATIONS			<i>Y</i> :	8		2	
3.	STANDARD PATTERN		T ***	€0			4	
4.	MATERIAL	*			*		4	
5.	MANUFACTURE		\$00 \$0	6) (8) (5)		1	6	
6.	DIMENSIONS	£3					7	
7.	WORKMANSHIP AND FINISH	27					7	
8.	MARKING						7	
9.	PRE-INSPECTION OF STORES	S/CONSIG	NMENT		80 22		7	
10.	QUALITY ASSURANCE		*		5 8		8	
11.	SAMPLING						8	
12.	CRITERIA FOR CONFORMITY		and and and pro-				10	-7
13.	WARRANTY					20	10	
	PACKAGING		* * *		6		11	
	DEFENCE STORES CATALOGUE	E NUMBER	}				13	
	SUGGESTIONS FOR IMPROVE	•					13	
	APPENDICES 'A' & 'B'			k.	14	&	15	
	DRAWING						16	
	DIMITING							

(iv)

JSS 8415-09:2000 Acert Stands
(Revision No. 21 1975) 57 187

0. FOREWORD

- 0.1 This specification has been prepared by the Stores Standardisation. Sub Committee on the authority of the Standardisation Committee, Ministry of Defence.
- 0.2 This specification has been approved by the Ministry of Defence and is mandatory for use by the Defence Services.
- 0.3 This specification is a revision of JSS 8415-09:
 - 0.4 This specification would be used to guide manufacture, quality assurance and procurement of the items.
 - Quality Assurance Authorities for the items covered by this specification are CQA(T&C), Kanpur; DQA(N), New Delhi and JDQAS(Aero), New Delhi for Army, Navy and Air Force respectively. Enquiries regarding this specification, relating to any contractual conditions, shall be addressed to the Quality Assurance Authority named in the tender or contract. Other enquiries shall be referred to:-


The Director,
Directorate of Standardisation,
Ministry of Defence,
'H' Block, DHQ PO,
New Delhi - 110 011.

0.6 Copies of this specification can be obtained on payment from :-

The Controller, Controllerate of Quality Assurance (Textiles & Clothing), Post Box No. 294 Kanpur - 208 001.

0.7 This specification holds good only for the supply order for which it is issued.

JSS 8415-09:2000 . (Revision No.2)



1. SCOPE

This specification covers the requirements of Gloves, Leather, White, Lined intended to be used for protection of hands against cold, wind and snow in extreme cold climates. The gloves are made in two separate detachable layers, having three compartments and are used complete with detachable liner.

2. RELATED SPECIFICATIONS

2.1 Reference is made in this specification to :-

/ IS 539:1974 / Naphthalene (second revision) (Amendment 1) Reaffirmed 1993 2000

/ IS 1095:1991 / Handloom cotton dress materials, bleached, dyed, printed, striped. or checked (first revision) RA-2002

IS 4905:1968 Methods for random sampling (Amendment 1) / Reaffirmed 1991 2001

Chrome leather for high altitude gloves (first revision)

Reaffirmed 19972003

Austr. Director

JSS 8415-09:2000 (Revision No.2)

Cotton webbing for personal web equipment (second revision) 32 Revision Reaffirmed 1992 Too 4

IS 8156:1994 Fasteners, for consumer goods-synthetic hook and loop tape (second revision)

IS 8331:1993 Textiles-angola shirting (first levision), Aurols-1

IND/GS/799 Liner waterproof bag

IND/TC/0108 Pile fabric (woven)

IND/TC/0321(h) Tape cotton white, 6 mm

IND/TC/2284(a) Press button (titch type), white

JSS 8135-10:1996 Polypropylene strapping, 12 mm wide

CQA(GS)/US/460 Boxes fibreboard rigid corrugated triple wall 7 ply

2.2 Copies of the Indian Standards are obtainable on payment from :-

Bureau of Indian Standards, Manak Bhavan, 9, Bahadur Shai Zafar Marg, New Delhi - 110 002

or

their regional/branch offices.

2.3 Copies of JSS 8135-10, IND/GS series of specification and COA(GS)/US/460 are obtainable on payment from :-

The Controller, Controllerate of Quality Assurance (General Stores), Post Box No. 127, Kanpur - 208 001.

REST. Director (*)

Austr. Director (*)

Inactorate of Stark

JSS 8415-09:2000 (Revision No.2)

2.4 Copies of IND/TC series of specification are obtainable on payment from :-

The Controller, Controllerate of Quality Assurance (Textiles & Clothing), Post Box No. 294, Kanpur - 208 001.

STANDARD PATTERN


3.1 The standard pattern of Gloves, Leather, White, Lined is held by the Controller, Controllerate of Quality Assurance (Textiles & Clothing), Post Box No.294, Kanpur - 208 001 and shall constitute the standard as regards any particulars or properties not noted/defined in this specification.

4. MATERIAL

4.1 The gloves shall be manufactured from the following materials:-


4.1.1 OUTER

Com	ponent	Material		Methods (refer to)
	1	2		3
(a)	Outer complete with Gussets, cuffs fingers and gauntlet portion	Leather, chrome, sheep/goat, white pigment finish, water-proof	*	IS 5866
(b)	Lining for Index finger, right hand	Shirting Angola drab	e.	IS 8331
(c)	piece of the slit	Selvedge of cambric cotton, white or Long cloth, white	(s	IS 1095 ee note below) IS 187
(d)	Snap fastener for closing of slit on the Right hand	(Titch type),	•	IND/TC/2284(a)



(e) Straps for adjustment at wrist	Web, cotton, thin, 20 mm, white	IS 6488
(f) Loop for passing the straps	Tape cotton, 6 mm, white	IND/TC/0321(h)
(g) Fastner synthetic tape	Hook/loop fastner synthetic tape, 20 mm wide, white	IS 8156
(h) Sewings	Sewing cotton, 165 d tex x 6, white	IS 1720
4.1.2 LINER		E1 58
(a) Inner Lining		
i) Body, gusset,		IS 1095
cuff, Index finger and Thumb	White or Long cloth, white	IS 187
	Sewing cotton 100 d tex x 6, white	IS 1720
(b) Outer lining		
i) Outer hand, cuff, thumb	Pile fabric, 6 mm (woven)	IND/TC/0108
ii) Palm sidə	Pile fabric, 3 mm (woven)	IND/TC/0108
<pre>iii) Gussets and left Index finger</pre>	Shirting angola drab	IS 8331
iv) Sewings	Sewing cotton, 165 d tex x 6, white	IS 1720


Note: The selvedge portion of `cambric cotton, white' used for the body of the `inner lining' shall be utilised for the edging tape at the slit of the right Index finger (outer)



JSS 8415-09:2000 (Revision No.2)

MANUFACTURE

- 5.1 The gloves shall be made in two separate layers viz, outer layer of white leather and inner layer made from various materials as indicated in clause 4. The inner liner shall also be made in two layers.
- or goat skin white, chrome tanned, treated for water-proofness with aluminium stearate. The gloves shall have three compartments to accommodate thumb, index finger and remaining three fingers in one compartment. The index finger of the right hand shall be provided with a slanting slit fitted with a press button as shown in the drawing attached. Edging tape shall be provided in the top layer of the slit to avoid stretching of leather and wide opening of slit. Gauntlet portion shall be in one piece and secured with the body at wrist with two rows of machine stitching.
- 5.1.1.1 Side piece (towards the little finger) and the fourchette shall be attached to the glove as shown in the drawing. The palm side of the Index finger shall be lined with shirting Angola. All the components shall be assembled with the type of seams as shown in the drawing. The seams shall be sealed with an approved sealing compound by the Quality Assurance Officer.
- 5.1.1.2 An adjustment strap of thin web shall be fitted with hook and loop fastner synthetic tape, 20 mm wide. Hook tape fastner of 4 cm length should be stitched on the edge of thin web and loop tape fastner of 7 cm length should be stitched on palm side of web as shown in the drawing.
- 5.1.2 Liner Liner shall be made by using the thicker pile fabric on back side and the lighter pile fabric on palm side lined with `cambric, cotton, white or long cloth white'.
- b.1.2.1 The right index finger shall not be made up to the tip but finished at the base of the fingers as shown in the drawing attached. The left Index finger shall be made from 'shirting angola'. The liner shall be assembled with the type of seams as shown in the drawing attached.
- 5.1.2.2 The bottom edge of the liner, the lining material shall be extended out to come over the pile fabric and stitched with raw edges turned in to form a 6 mm binding as shown in the drawing.



5.1.3 Sewing - The gloves shall be assembled throughout with lock stitch regulated at not less than 27 stitches and not more then 42 stitches per dm for the leather and 36 stitches per dm for liner to the glove. All stitches shall be of even tension throughout and all loose ends securely fastened off.

6. DIMENSIONS

6.1 The dimensions of the gloves (outer and liner) shall conform to the details given in Appendix 'A' and 'B'.

7. WORKMANSHIP AND FINISH

TO THE PARTY OF TH


7.1 In appearance, general workmanship and finish and in all other respects not noted or defined in this specification, the gloves shall conform to the standard pattern.

8. MARKING

8.1 Each pair of gloves prior to being offered for inspection, shall have a white cloth label of suitable size securely sewn on the inside over the 'cambric cotton' at the cuff, on which the manufacturer shall mark legibly and indelibly his name, initials or recognised trade mark, DS Cat Number, year of manufacture and size of glove (small, medium or large).

9. PRE-INSPECTION OF STORES/CONSIGNMENT

Manufacturer/contractor must satisfy themselves that the stores are in accordance with the terms of the contract and fully conform to the required specification, by carrying out a thorough pre-inspection of each lot before actually tendering the same for inspection to the Quality Assurance Officer nominated under the terms of the contract. A declaration by the contractor that a necessary pre-inspection has been carried out on the stores tendered, will be submitted alongwith the challan. The declaration will also indicate the methods followed in carrying out pre-inspection showing the features checked/tested and will have the test certificate attached to the challan/declaration.



JSS <u>8415-09:2000</u> (Revision No.2)

9.2 If the Quality Assurance Officer finds that pre-inspection of the consignment as required above has not been carried out, the consignment is liable for rejection.

10. QUALITY ASSURANCE


10.1 On examination, the sample, taken from any portion of the consignent, shall conform to the requirements when tested in accordance with the methods mentioned against each in this specification.

11 SAMPLING

- 11.1 The suppliers shall arrange the units of the homogeneous lot in such a way that all the units are easily accessible to the Quality Assurance Officer to enable him to draw mamples from any portion of the homogeneous lot.
- 11.2 Sampling of stores shall be done by adopting appropriate sampling method as per IS 4905 so that samples drawn as per respective column 2 of sampling plan given for assessing various quality requirements are truly representative of the lot.

11.3 Scale of Sampling

11.3.1 The number of sample units to be drawn for assessing the quality of the store, characteristicwise should be in accordance with the column 2 for dimensional/non-destructive/visual inspection, column 4 for detailed laboratory testing and column 6 for chemical and other time consuming testing parameters. Table alongwith necessary explanation is given below.



JSS 8415-09:2000 (Revision No.2)


TABLE

SAMPLING PLAN FOR GLOVES LEATHER WHITE LINED Based on AQL of 4% (Authority ISO: 2859)

					1. •	right trivia	racy ,	PO1: 702A	L						
tarms like	of s	define amples f Boxe 40 pa	unit s		Sampling Plan for GLOVES LEATHER WHITE LINED										
Boxes 40 pa:	cont	aining		Vis	Visual Physical Chemical Param Parameters Parameters and other physical (for Non parameters * req Destructi - long testing to ve Parame - (for laborator ters) tests)										
			9 S	ibTe	tance	ple	Acce- ptan- ce No	Sample Size	Acceptance No.						
	1			2	3	4	5	6	7						
Relow	<u> </u>	150		13	1	13	1 1	3	0						
151	(-	280	. :	13	1 :	13	; 1	5 !	l. ₀ .						
281	81 - 500				2	! 13	1	5							
501	01 - 1200				5 {	¹ .20	2	5	0						
1201	<u> </u>	3200		50 {	5	32	3	13	1						

*Time consuming physical parameters are

- (i) All physical & chemical tests of Leather material possible to be carried out on specimen's retrieved from the made up store.
- (ii) Constructional details (ends, picks, mass & weave) of fabric and web cotton.
- (iii) Composition (wool) in shirting Angola.
 - (iv) Pile fabric-all parameters except B.S.
 - (v) Hooks/loops fastener-all parameter except colour fastness.



JSS 8415-09:2000 (Revision No.2)

Note: -


- (i) Quality Assurance Officer will select sampling units randomly and select one ultimate item from each sampling unit i.e.one box so as to make desired sample size as given in column 2.
- (ii) Samples for laboratory testing will be drawn from the samples drawn as mentioned in column 2 only.
- (iii) For chemical parameters samples to be drawn at random as per IS 4905 from those samples drawn as per column 4.

12. CRITERIA FOR CONFORMITY

- The Quality Assurance Officer shall first draw the samples for visual examination as per column 2 of the sampling plan and a quality assurance report will be prepared by him.
- 12.2 If found satisfactory on visual inspection, the Quality Assurance Officer shall draw samples for laboratory tests as per scale for physical parameters depending upon the level of quality assurance.
- 12.3 The samples for Chemical tests and Time consuming tests will form a part of samples drawn for physical laboratory tests.
- 12.4 The number of sample units to be sampled for laboratory testing should be a multiple of the number of characteristics/tests which cannot be carried out simultaneously on the same sample units.

13. WARRANTY

13.1 The stores supplied against this specification shall be deemed to bear the warranty of the contractor against defective design, material, workmanship and performance for a period of 12 months from the date of receipt of stores at consignee's depot. If during this period, the stores supplied are found to be so defective, the same shall be replaced immediately with the serviceable stores by the contractor at site free of any charges or cost.



JSS 8415-09:2000: (Revision No.2)

14. PACKAGING

13

14.1 The following materials shall be used for the packing of Gloves, Leather, White, Lined:-

Material


Conforming to

,		
/ i)	Polyethylene film, 0.04 mm thick	IS 2508
(ii) /	Double walled corrugated fibreboard boxes 7 ply (Outer liner shall be laminated with polyethylene film to provide water-proofness).	IS 2771(Part 1)
111)	Polypropylene strapping, 12 mm wide	JSS 8135-10
iv)	Paper cuttings or Any other suitable cushioning material	Best trade quality to be approved by the Quality Assurance
vi)	Preservatives	IS 539
	No. 1	the state of the s

15.2 Method

15.2.1 The store shall be supplied in a new, clean, dry and sound condition and accepted store duly preserved shall be packed. Store of only one size shall be packed in the same backage.

1b.2.2 Each pair of gloves duly treated with preservative shall be placed in a polyethylene film bag of suitable size and then heat sealed. Forty (40) such individual pairs shall then be packed in box libreboard rigid corrugated triple wall 7 ply of appropriate size. The boxes shall be lined with waterproof liner to avoid ingress of maleture. Empty space inside the box shall be filled with suitable rushioning material to avoid movement of the contents during transit.



JSS 8415-09:2000 (Revision No.2)


- 15.2.3 The boxes shall be securely bound with at least two bands of polypropylene strappings. Each band of polypropylene strapping shall be of one complete piece and the ends shall be sealed with machine.
- 15.2.4 During packaging the contents shall not be subjected to undue compression or distortion.
- 15.2.5 The gross mass of the package shall not exceed 40 kg.

15.3 Marking

- 15.3.1 Before despatch each box shall be legibly and indelibly marked with indelible ink as per details given gilew:
 - (a) Front and Top
 - (i) DS Cat number and nomenclature of the store(ii) Quantity packed preceded by abbreviation 'QTY'
 - (b) Back
 - (i) Name and address of the consignee

(ii) Mass in package in kg

- (iii) Number of individual package and total number of packages in a consignment e.g. 1 of 4, 2 of 4, 3 of 4 and 4 of 4 when the consignment consists of 4 pacakges.
- (c) Left End
 - (i) Consignor's name and address
- (ii) Month and year of packing
- (iii) Inspection Note No. and date
- (iv) A/T, S/O or extract number and date



16. DEFENCE STORES CATALOGUE NUMBER

16.1 This specification shall govern manufacture/inspection of the following stores:

DS_	CAT N	o <u>.</u>	NC	MENCL	ATUR	E		1000 E	**	
841	5-000	.176	G] (O	loves, BSOLE	Lea SCEN	ther, T)	White,	Lined,	Small	
	-000	177		w , :	11		. "		Medium	n
0.1	-000	178	9	11 .	11	38	11	I	arge	
				k. +						

17. SUGGESTIONS FOR IMPROVEMENT

17.1 Any suggestions for improvement in this document may be forwarded to:-

The Director,
Directorate of Standardisation,
Ministry of Defence,
'H' Block, DHQ PO,
New Delhi - 110 011.

(Revision No.2)

SIZE SCALE FOR GLOVES LEATHER WHITE, LINED-OUTER


Asset. Directories A o Asset. Directories of Stando

1 4	1	Over	1	Uidth	1	Wic	lt h	οĖ	:	Dent	հ :	Th	um	 b	, .	ndex	F	inge	-!			ment		Length o
,		911																						strap at
	1	lengti	11	palm	1.	Top	1	Botto	'ac	cuff	1 2	111.	1		:		:		: 1	three	f	inger	s 1	urist
	1		1		1	Edg	je l	Edge	١.		} :	lengt	h!		1		;		. ;	Lengt	h!	Width	;	
ř	1	cn'	1	cn	!		. d	cn	1	כם	1	CA	:	 са	:	ca ca	:	ca.	1	. ca	;	C:3	 1	 CD
9 . •	I	2	1	3	ľ	4	1	5	. 1	6	1,	7		8	;	9	1	10	.;	. 11	;	12	1	13
•	1	·····································	1		1		1		1		1.				;		;		1		1			
hot t	1	34.5	1	14.5	1.	15.	0:	21.5	1	11	i	14	. !	6.00	:	7.5	!	4.7	1	8	:	10.5	:	45
je 1 11.1	1	37.0	1	15.0	1	15.	51	22.0	1	12	1	15	1	6.50	;	B.5.	į	5.0	1	. 9	;	11.5	١,	45
	1	30.5	1	15.5	1	16-	0!	22.5	. !	13	:	16	. ! !	7.0	. !	9.5	:	5.3	1	10	;	13.0	!	45
!	i		1		:		1	;0	į			†	ì	,	;	7.0	1	0.0	i		;	10.0	}.	43
	ı	40.5	1	<u>+</u> 0.3	;	_	 !	±0.3	1	_	:	±0.3	1	_	- ;	_	;		1		1	_	1	±1.0
place 1	1		1		:		. ;		ł	• •	1.		1		5		:		;		;		1	

JSS 84-15-09:2000 (Revision No.

i f f f f		AOver all leng	l h	Widt acro: palm	1 I Op	I Bot	Dep of toalcuf	5 1-77			11	Index Fength or eft hand	19	ger Kidt	IP I	he r	etaent eaainin finger
75 m (m)m		~~~~			! cm.		60 (Con. con.	: cm		CM.	 :		 !			CH	h:Width
1		. 2 -		3	1,'4	1 5	: 6	1 7	:	8	-1	9.	 :	10	 !	11	
PEDIUN	1	33-0	1	13.5	113.5	20.0	110.5	1	1		!	7	;	4.2	1.		1 9.5
VHOE	1		1		1 1		111.5 1 112.5	114.5	;	6.0	,	. 8	;	4.5	1	8.5	1. 10.5
 () E =-					· .		172.5	115.5 1	1.	6.5	1	9	 -	4.8	; ;	9.5	12.0
AHCE	!	±0.3	1	+0.3	!±0.3!	-	1.7.1	1 -:	;	_	:	-	;	-	 !		

4.5



...d

18... 28.8.08 रा अन्ताः १का

: natry of Defence

JSS 8415-09:2000 Revision No. 2 (Reaffirmed 2008)

र्शिक नियंशका (तकावसम्ब) Keett, Disentor (T.C.)

मानकी करण निद्यालय mirectorate of Standardisation

च्छा मन्त्रालय, नई दिल्ली,

Min. of Delance, New Delbi-1

REAFFIRMED WITH THE MODIFICATIONS

1. On all pages :-

For

JSS: 8415-09:2000

Read

(Revision No 2) JSS: 8415-09: 2000

(Revision No 2) (Reaffirmed 2008)

2. Page 1, Para 0.5 and page 13, Para 17.1

For

DHQ PO,

Nirman Bhavan PO.

3. Page 1 Para 0.6 :-

For

The Controller,

Controllerate of Quality Assurance (T&C)

Post Box No 294, Kanpur - 208 001.

Read

The Director'

Directorate of Standardisation

Ministry of Dfence

'J' Block, Room No 5, Nirman Bhavan PO,

New Delhi - 110 011

JSS 8415-09: 20 08

RevisioNo2

Page 2, Sub clause 2.1 Reference is made in this specification to :- (Reaffirmed 2008)

(a) IS 187:1978 Specification for Cotton Long Cloth

(Second Revision) Reaffirmed 2003

Amds 2

हायक निदंशक (धकाताः .. Asstt. Dir ector (T.C.) मानकीय रण निदेश।लश birectors - of Standardies -

ए**ला** मन्द्रः गा, नई द्विष् We nother what

(b) IS 539:1974

Specification for Naphthalene

(Second Revision) Reaffirmed 2005

Amd 1

(c) IS 1095: 1991 -

Handloom cotton dress materials, bleached, dyed, printed, striped or checked (superseding IS 861:1983, IS1098:1957, IS 1240:1958 and

IS 1556:1960) (First Revision) Reaffirmed 2007

(d) IS 1720: 1978 -

Specification for Cotton Sewing Threads

(First Revision) Reaffirmed 2002

(e) IS 2508: 1984 -

Specification for Low Density Polyethylene

Films Low density polyethylene

(Second Revision) Reaffirmed 2003

Amds 2

(f) IS 2771 (Part 1) -

Corrugated Fibreboard Boxes - - Part 1:

General Requirements (Second Revision) Reaffirmed 2002 Amds 2

(g) 4905: 1968

Methods for random sampling

Reaffirmed 2006

Amd 1

(h) IS 5866: 1979 -

Specification for Chrome Leather for High

Altitude Gloves Chrome leather.

(First Revision) Reaffirmed 2003

Amd 1

| JSS 8415-09:2000 | Revision No 2 | (Reaffirmed 2008)

(j) IS 6488: 1999 -

Cotton Webbing for Personal Web Equipment Specification (Third Revision) Reaffirmed 2004

(k) IS 8156: 1994 -

Fasteners for consumer goods-synthetic hook and loop tape, specification (Third Revision)
Reaffirmed 2004

(1) IS 8331:1993 -

Textiles -angola shirting (Second Revision) Amds 2

IND/GS/799

Liner waterproof bag

IND/TC/0108-

Pile fabric (woven)

IND/TC/0321(h) -

Tape Cotton white, 6 mm

IND /TC/ 2284 (a)-

Press button (titch type),

white

JSS 8135-10:2004-

Polypropylene strapping, 12 mm wide

CQA(GS)/US/460

Boxes fibre board rigid corrugated triple wall 7 ply

RAKSHA MANTRALAYA/MINISTRY OF DEFENCE

AMANAKIKARAN NIDESHALAYA/DTE OF STANDARDISATION TAIRE TO THE TAIL THE TEN siry of Defeudes Poord/Sta Jated

अहायक क्रिलेशक (सक्छक्र) १९४४ मा शास्त्र पाट.) बानकीकरण निष्यालय बसा मन्त्रान्त्र, कई दिल्ली, din. of Defence, Now Belbi-भ Pirectorate of Standardisation

(STORES STANDARDISATION SUB COMMITTEE)

Amendment 1

Dec 2009

The following amendment is approved: -

Authority: As shown in Col 4 No. of sheet: (One)

Г	1				
Authority for	Amendment 4	S / 7497 / TC-13 dt 17 Sep 2009			
/ Details of Amendment		under:- Sub clause 4.1.2 under heading Liner, Sr (iii) as S/7497/TC-13 dt	For Existing	Read Gussets And Left Shirting Angola IS 8331 Index Finger Drab Type I or II	
Nomenclature	Gloves , Leather, White Tined				
JSS & Year	JSS 8415-09:2000	(100 2000) CHEWNOLD	, .		