

GOVERNMENT OF INDIA
(Ministry of Home Affairs)
DIRECTORATE GENERAL
CENTRAL RESERVE POLICE FORCE
EAST BLOCK-7, SEC-1, R.K. PURAM, NEW DELHI-110066
Email:- comncell@crpf.gov.in Tele Fax:011-26107493

No. B.V-7/2019-20-C (GABP)

Dated, the 29th May'2019


To

DIG (Prov), BSF
Block No. 10, CGO Complex
Lodhi Road, New Delhi-03

Subject: Regarding QRs/TDs of "Server for GABP".

Please find enclosed here with QRs and TDs in respect of "Server for GABP" as per Annexure-A duly approved by the competent authority for further necessary action.

Encl: (QRs & TDs of Server for GABP).


{P.R.Jha, DC (Comn)}
For DIG (Equipment)
Directorate General, CRPF
dc 29/5

GRS/STDS OF PROCUREMENT OF 01 NO SERVER FOR GABP, MONGOLIA

Srl No	Name	Details	Unit	Remarks	Trial Directives
01.	Integration Server	Minimum number of Virtual Machines offered per node Number of VCPUs (Physical cores) offered per virtual machine RAM (Memory) offered per virtual Machine(GB) Storage offered per virtual Machine (GB) Hypervisor to be Integrated with SDS Integration with Third party FC storage Number of Years of service and support from OEM(A) HCI to be software defined or hardware defined HCI Support If other, indicate HCI support	24 500 GB Within Kernel, outside Kernel Others 5 Years Software defined VMWare	Committee is of the opinion that during time of tender, if same model is not available, the latest model of similar configuration or substantially equivalent model may be accepted.	All parameters as per Technical specification will be verified with the help of OEM data sheet of offered product. Any deviation in product specification from OEM data sheet is liable to be rejected.

Amulya Arora

BA

GA

1-1

Amulya

Dr

K. Jank

Dr

		If other, specify	1. Each node should be configured with 2x intel xeon Gold 5120 CPU. Inline deduplication and compression functionality should be enabled from day one.
02.	Other Parameters	Types of ports offered per node	10 GBPS : 10 GBase-SFP
		Compression & Deduplication on Disks	SSD only
		External FC storage connectivity	True
		The length of cable connecting the nodes to the switch (mtrs)	5
		Automated disaster Recovery Orchestration	True
03.	DBMS	VM-Centric policy-Based management	True
		Installation, configuration, Migration of application and database from existing hardware, Demonstration	True
		Oracle 12c DBMS Enterprise Edition	each
04.	Middleware	-1 Processor License	
		-RAC(Real Application Cluster)	
05.	Storage	TMAX Middleware	Each
		-(Load Balancing) -- - 200 User License	
Network Device		NetApp FAS3220A Usable 10TB (RAID 6)	Set
06	SAN Switch	BROCADE BR300 8G 16 port SAN Switch	Each
	L4 Switch	Piolink PAS-K2424 L4 Switch	Each

All parameters as per Technical specification will be verified with the help of OEM data sheet of offered product. Any deviation in product specification from OEM data sheet is liable to be rejected.

Committee is of the opinion that during time of tender, if same model is not available, the latest model of similar configuration or substantially equivalents model may be accepted.

Approved by: *[Signature]*
 Date: *[Signature]*
[Signature]
[Signature]
[Signature]
[Signature]

