# GOVERNMENT OF INDIA (Ministry of Home Affairs) DIRECTORATE GENERAL CENTRAL RESERVE POLICE FORCE EAST BLOCK-7, SEC-1, R.K. PURAM, NEW DELHI-110066

Email:- comncell@crpf.gov.in Tel

Tele Fax:011-26107493

No. B.V-7/2018-19-C (BGAN) To

- Dated, the // Dec'2018
- DIG (Comn), ITBP
   Block No. 2, CGO Complex
   Lodhi Road, New Delhi-03
- 2. DIG (Comn), NSG Meharam Nagar Palam, New Delhi-37
- 3. DIG (Comn), SSB East Block-V, R.K Puram New- Delhi-66
- 4. AIG (Comn), CISF Block No. 13, CGO, Complex Lodhi Road, New Delhi-03
- 5. DIG (Prov), BSF Block No. 10, CGO Complex Lodhi Road, New Delhi-03
- 6. Liaison Office, Assam Rifle Room No-171, North Block, MHA New Delhi -01

#### Subject: Regarding QRs/TDs of BGAN (Broadband Global Area Network).

Please find enclosed here with QRs and TDs in respect of BGAN (Broadband Global Area Network) as per Annexure-A & Annexure-B respectively duly approved by the competent authority for further necessary action.

Encl: (QRs & TDs of of BGAN (Broadband Global Area Network)).

{P.R.Jha, DC (Comn)}
For DIGP (Equipment)

Directorate General, CRPF

## QRs FOR MAN PORTABLE SATELLITE PHONE BGAN (STATIC)

SN	Parameters	Specification
Gene	ral Character	
(21)	User Interface	Interactive LCD/LED or better Display.
(b)	Languages	English
(c)	Weight (including battery)	≤3.5Kg
Data	Capabilities.	
(d)	Standard IP	280 Kbps or more (As per user requirement)
(e)	Streaming IP	64/128 Kbps or more (As per user requirement)
Voice	Capabilities.	
(f)	Standard Voice	4kbps
(g)	Services	Required essential BGAN services i.e. Voice, Fax, SMS & Data Streaming
Inter	faces.	
(h)	Ports	Any two of following ports - RJ45, RJ11 and USB
Envi	ronmental Conditions.	
Temp	perature.	
(i)	Operational (ambient)	-25°C to +55°C
(j)	Storage	-25°C to +55°C(with battery) -25°C to +60°C(Without battery)
(k)	Relative Humidity	95% non-condensing at +40-C
(1)	Robustness	MIL-STD -810B or better
(m)	Water and Dust (IP-rating)	IP-54 or better
AC/I	OC power supply.	
(aa)	Input	100-240VAC, 10.5-32VDC
(ab)	Built-In-Battery	Rechargeable Battery
(ac)	Transmit time / Receive time / Stand-by-time	(1:1:12) Tx Time: 2Hrs or more Rx Time:- 2 Hrs or more Stand by time:24 Hrs

Madren To

the for

Pays Joh

SN	Parameters	Specification	
Packa	ige		
(i)	BGAN Transceiv	ver	
(ii)	Build-in-Rechargeable battery		
(iii)	Soft bag		
(iv)	USB to Etherne	t Convertible Cable	
	(To be provided o	only for terminals with USB interface)	
(v)	Power Supply A	dopter	
(vi)	English Langua	ge Quick Start guide	
(vii)	English langua	ge web server and embedded manual (ENG)	
(viii)	Car charger cal	ble	
Term	s & Conditions		
(al)	Connectivity	During tendering the vendor will specify how they are going to provide satellite communication service. They will also specify terms and condition and vendor will have to ensure end to end connectivity.	
(am)	license	Vendor to have Valid DPL (Dealer Possession License)	
(an)	AMC	Vendor must provide AMC for this after warranty for 5 yr.	
(ao)	Warranty	3 years warranty must be produce by vendor	
(ap)	Miscellaneous	<ul> <li>(i) User manual shall be provided by the vendor.</li> <li>(ii) Regional/local service center for repair/maintenance of equipment and warranty/post warranty service center should be available in India and a list of available service center in India may also be attached by the vendor.</li> <li>(iii) Vendor should have minimum 3yr experiences in supplying INMARSAT Land SATCOM terminals and to be submitting proof of past supplies.</li> <li>(iv) The bidders are to submit a MAF (Manufacturer's Authorization form) by along with the bid. In case the OEM has a direct or</li> </ul>	

Make I

the Market Marke

any of

Porj &

## QRs FOR MAN PORTABLE SATELLITE PHONE BGAN (VEHICLE BASED)

SN	Parameters	Specification		
Gen	eral Character			
a)	User Interface	Interactive l	Interactive LCD/LED or better Display.	
b)	Languages	English		
Spec	cification.			
Wei	Control of the Contro			
(c)	Transceiver	2.5 kg ± 10%	6	
(d)	Antenna	≤6 Kg		
	al services.			
(e)	Voice	4kbps		
(f)	Standard IP	464 Kbps or	more	
624	No transcriberation	(As per user	requirement)	
(g)	Streaming IP	128/256 Kb	ops or more	
1.00	ADDIONAL INC.	(As per user	(As per user requirement)	
(h)	SMS	the second second second	ters or more	
(i)	Services	Required essential BGAN services i.e. Voice, Fax, SMS & Data Streaming		
Inte	erfaces.			
(i)	2 X Analogue RJ-1	1 Phone/Fax	interfaces	
(k)	4 X LAN interfaces	AND RESIDENCE AN		
(1)	Connector type	RJ-45 Power over	Ethernet (PoE)	
(m)	Data rate	10/100 Mb	ps	
(n)	Max. cable length	100m/ 328	ft (cat5 UTP)	
[0]	Standard	ISO/IEC/E	N Standards	
(p)	1 X ISDN interface	1 X ISDN interface		
(q)	Connector type	RJ-45		
(r)	BGAN SIM Card slot			
11000	Power.			
	(i) DC Input range	9	10.5-32VDC	
	(ii) Power (max)@		150W (incl. antenna & PoE output)	

Wholes the

Jan May

SN	Par	Parameters Specification		
	-	ital Condi	ions.	
(ab)	The second line and the second	erature		
Operational		1.1	-25 to +55∘C	
	Surviv		-40 to +80°C	
	Storag	ge	-25°C to +55°C(with battery)	
	THE PARTY NAMED IN	***	-25°C to +60°C(Without battery)	
(ac)	Relati		95% non-condensing at +40°C	
(ad)	Water	and Dust	(IP-rating)	
	Trans	ceiver	IP30 or better	
	Anten	ina	IP56	
Othe	er Feat	ures.		
(ae)	Telephone Phone book, message indication, restricted			
Functionality		tionality	dialing and traffic logging	
PAC	KAGE.			
	(i)	Vehicular	BGAN transceiver	
	(ii)	Vehicular	r BGAN tracking antenna	
	(iii)	Antenna	cable	
	(iv)	55-4500 37 43 43 43 50	Ethernet cable	
	(v)	24V DC i	put cable with required connectors	
	(vi)		mounting kit (fixed/ rail)	
	(vii)	Getting S	Started kit Quick start guide, CD with manual	
Terr	ms & C	onditions		
(ag)	Conn	ectivity	During tendering the vendor will specify how they are going to provide satellite communication service. They will also specify terms and condition and vendor will have to ensure end to end connectivity.	
(ah)			Vendor to have Valid DPL (Dealer Possession License).	
(ai)	AMC		Vendor must provide AMC for this after warranty for 5 yr.	
(aj)	Warr	anty	3 years warranty must be produce by vendor	

King To

John Part

SN	Parameters	Specification
(ak)	Miscellaneous	(i) User manual shall be provided by the vendor.  (ii) Regional/local service center for repair/maintenance of equipment and warranty/post warranty service center should be available in India and a list of available service center in India may also be attached by the vendor.
		(iii) Vendor should minimum have 3 yr experience in supplying Inmarsat Land SATCOM terminals and to be submitting proof of past supplies.
		(iv) The bidders are to submit a MAF (Manufacturer's Authorization form) by along with the bid. In case the OEM has a direct or indirect subsidiary in India. Bidders are to submit MAF issued by the direct or indirect OEM's Indian subsidiary. (v) Log book to be provided by vendor.

WO/RM R.S. Dhaka Assam Rifles

AC-II M.K Verma NSG

Baljit Singh, INSP(Comn) BSF P.S. Meena, AC(Comn)

SSB

R.K. Meel, DC CISF

P.R.Jha, DC(Comn) CRPF

Capt. VIG. lyer BPR&D

6/w

Harjinder Singh, DIG(Eqpt)

CRPF

D.S.Rawat, DIG(Comn) CRPF

Raju Bhargava, IPS, IGP(Comn &IT) CRPF

Md. Jawed Akhtar, IPS, ADG (Work & Comn), CRPF

Approved/Not Approved

Rajeev Rai Bhatnagar, IPS DG, CRPF

### TRIAL DIRECTIVE FOR MAN PORTABLE SATELLITE PHONE BGAN (STATIC)

SN	Parameters	Specification	Trial Procedure	
Gen	eral Character			
(a)	User Interface	Interactive LCD/LED or better Display.	Board will check practically.	
(b)	Languages	English		
(c)	Weight (including battery)	≤3.5Kg	Board will check practically.	
Data	Capabilities.			
(d)	Standard IP	280 Kbps or more (As per user requirement)	Board will check practically.	
(e)	Streaming IP	64/128 Kbps or more (As per user requirement)		
Voic	e Capabilities.			
(f)	Standard Voice	4kbps	Firm will submit OEM	
(g)	Services	Required essential BGAN services i.e. Voice, Fax, SMS & Data Streaming	Certificate.	
Inter	rfaces:			
(h)	Ports	Any two of following ports:- RJ45, RJ11 and USB	Board will check practically.	
Envi	ronmental Condi	itions.		
Tem	perature.			
(i)	Operational (ambient)	-25°C to +55°C	Firm will submit OEM certificate	
(j)	Storage	-25°C to +55°C (with battery) -25°C to +60°C (Without battery)		

Ky to

Jest May de

SN	Parameters	-2- Specification	Trial Procedure
(k)	Relative Humidity	95% non-condensing at +40-C	Firm will submit
(1)	Robustness	MIL-STD-810B or better	- OBM certificate
(m)	Water and Dust (IP-rating)	IP-54 or better	
AC/	DC power supply.		
(aa)	Input	100-240V AC, 10.5-32V DC	Firm will submit OEM certificate.
(ab)	Build-In- Battery	Lithium ion (rechargeable)	obsit certificate.
(ac)	Transmit time/ Receive time/Stand-by- time	(1:1:12), Tx time: 2Hrs or more Rx Time:- 2 Hrs or more Stand by time:24 Hrs	
Pack	tage		
(i)	BGAN Transceive	er	Board will check
(ii)	Built-in-Recharg		
(iii)	Soft bag	and a second	practically.
(iv)		Convertible Cable ly for terminals with USB interface)	
(v)	Power Supply Ad	opter	-
(vi)		e Quick Start guide	-
(vii)		ge web server and embedded	
(viii)	Car charger cable	е	
Term	s & Conditions		
(al)	Connectivity	During tendering the vendor will specify how they are going to provide satellite communication service. They will also specify terms and condition and vendor will have to ensure end to end connectivity.	
am)	license	Vendor to have Valid DPL (Dealer Possession License)	Firm will submit relevant document to
an)	AMC	Vendor must provide AMC for this after warranty for 5 yr.	the Board of officers.
ao)	Warranty	3 years warranty must be produce by vendor	

Kin Date of

Sont Pay de

SN	Parameters	Specification	Trial Procedure
(ap)	Miscellaneous	(i) User manual shall be provided by the vendor.  (ii) Regional/local service center for repair/maintenance of equipment and warranty/post warranty service center should be available in India and a list of available service center in India may also be attached by the vendor.  (iii) Vendor should have minimum 3yr experiences in supplying INMARSAT Land SATCOM terminals and to be submitting proof of past supplies.  (iv) The bidders are to submit a MAF (Manufacturer's Authorization form) by along with the bid. In case the OEM has a direct or indirect subsidiary in India. Bidders are to submit MAF issued by the direct or indirect OEM's Indian subsidiary.  (v)Log book to be provided by vendor.	Firm will submit relevant document to the Board of officers.

Jee De Mo

## TRIAL DIRECTIVE FOR MAN PORTABLE SATELLITE PHONE BGAN (VEHICLE BASED)

SN	Parameters	Specification	T-1-15	
Ge	neral Character	эростенной	Trial Procedure	
(a)	User Interface	Interactive LCD/LED or better	Board will chast "	
		Display.	Board will check practically.	
(p)	Languages	English		
-	cification.			
We	ight.			
(C)	Transceiver	2.5 kg ±10%	Board will check practically.	
(d)	Antenna	≤6 Kg	board will check practically,	
Glo	bal services.			
(e)	Voice	4kbps	Board will short	
(f)	Standard IP	464 Kbps or more	Board will check practically and firm will also submit	
		(As per user requirement)	OEM certificate.	
(g)	Streaming IP	128/256 Kbps or more	oba certificate.	
		(As per user requirement)		
(h)	SMS	160 characters or more		
(i)	Services	Required essential BGAN services i.e. Voice, Fax, SMS & Data Streaming		
Inte	rfaces.	- a canning		
(j)	2 X Analogue RJ	-11 Phone/Fax interfaces	D1 '''	
(k)	4 X LAN interface	es	Board will check practically	
(1)	Connector type	RJ-45	and firm will also submit OEM certificate.	
		Power over Ethernet (PoE)	OEM certificate.	
(m)	Data rate	10/100 Mbps		
(n)	Max. cable length	100m/ 328ft (cat5 UTP)		
(0)	Standard	ISO/IEC/EN Standards		
(p)	1 X ISDN interfac			
(q)	Connector type	RJ-45		
(r)	BGAN SIM Card s			
55	Don't officerd s	SIUL		

Benh Pay

SN	Parameters	Specific		
(aa)	Power.	Specification	Trial Procedure	
	(i) DC Input range	10.5-32VDC	Firm will submit OEA	
	(ii) Power 150W (incl. antenna & PoE output)	certificate.		
Env	ironmental Con	ditions		
(ab)	Temperature	THE STATE OF THE S		
	Operational	-25 to +80°C	Firm will submit OEM	
	Survival	-40 to +80°C	certificate.	
	Storage	-25°C to +55°C(with battery) -25°C to +60°C(Without battery)		
(ac)	Relative Humidity	95% non-condensing at +40°C	Firm will submit OEM	
(ad)	Water and Dust (IP-rating		certificate.	
	Transceiver			
	Antenna	IP56		
Other	Features.	10.9.0000		
(ae)	Telephone Functionality	Phone book, message indication, restricted dialing and traffic logging	Board will check practically and firm will also submit OEM	
PACK.	AGE.		certificate.	
(i)	Vehicular BGAI	V transceiver	D. I	
(ii)		V tracking antenna	Board will check practically.	
iii)	Antenna cable	antenna	p-sectionity.	
iv)	Standard Ether	net cable		
V)		able with required connectors		
vi)	Antenna mount	ing kit (fixed/ rail)		
vii)	Getting Started manual	kit Quick start guide, CD with		

The May de

	SN	Parameters	Specification	
	Tern	ns & Conditions	<u>=promention</u>	Trial Procedure
7	(ag)	Connectivity	During tendering the vendor will specify how they are going to provide satellite communication service. They will also specify terms and condition and vendor will have to ensure end to end connectivity.	
	(ah)	license	Vendor to have Valid DPL (Dealer Possession License).	Firm will submit relevant document to the Board of
	(ai)	AMC	Vendor must provide AMC for this after warranty for 5 yr.	officers.
	(aj)	Warranty	3 years warranty must be produce by vendor	
	(ak)	Miscellaneous	(i) User manual shall be provided by the vendor. (ii) Regional/local service center for repair/maintenance of equipment and warranty/post warranty service center should be available in India and a list of available service center in India may also be attached by the vendor.	Firm will submit relevant document to the Board of officers.

The May de A

		Specification	Trial Procedure
SN	Parameters	(iii) Vendor should have minimum 3yr experience in supplying Inmarsat Land SATCOM terminals and to be submitting proof of past supplies.  (iv) The bidders are to submit a MAF (Manufacturer's Authorization form) by along with the bid. In case the OEM has a direct or indirect subsidiary in India. Bidders are to submit MAF issued by the direct or indirect OEM's Indian subsidiary.  (v) Log book to be provided by vendor.	Firm will submit relevant document to the Board of officers.

WO/RM R.S. Dhaka Assam Rifles AC-II M.K Verma NSG Baljit Singh, INSP(Comn) BSF P.S. Meena, AC(Comn) SSB

R.K. Meel, DC CISF

P.R.Jha,DC(Comn) CRPF Capt. W.G. lyer BPR&D Harjinder Singh,DIG(Eqpt) CRPF

D.S.Rawar DIG(Comn) CRPF Raju Bhargava, IPS, IGP(Comn &IT)

Md. Jawed Akhtar, IPS. ADG (Work & Comn), CRPF

Approved/Not Approved

Rajeev Rai Bhatnagar, IPS DG, CRPF