No.C.VII.1/2015-ITW(QRs)-(6) /ऽ ५५ भारत सरकार/Government of India गृह मंत्रालय/Ministry of Home Affairs

पुलिस आधुनिकीकरण प्रभाग /Police Modernization Division

संभरण-। डेस्क /Prov.l Desk

Jaisalmer House, 26 Man Singh Road, New Delhi, dated the FÂug, 2015

To,

The DsG: AR, BSF, CISF, CRPF, ITBP, SSB, NSG & BPR&D.

Subject: QRs and Trial Directives of DSLAM 100 Subscribers.

Sir.

The undersigned is directed to refer to the subject mentioned above and to say that the QRs and Trial Directives in respect of DSLAM 100 Subscribers as per Annex- "A" and Annex- "B", respectively have been approved by the competent authority in MHA.

- 2. Henceforth, all the CAPFs should trial evaluate and procure the above item, required by them, strictly as per the laid down QRs.
- 3. Concerned CAPF will be accountable for correctness of the QRs and Trial Directives of DSLAM 100 Subscribers.

Yours faithfully

(M. N. Sukole)

Under Secretary to the Govt. of India

Encl: As above.

Copy forwarded for necessary action to:

USO (IT), MHA - with the request to host the QRs and Trial Directives of DSLAM 100 Subscribers on official website of MHA (under the page of Organizational Set up, Police Modernization Division-Communication Equipments).

Copy to: DDG (Procurement), MHA

(R.K. Soni)

Section Officer (Prov.I)

\sim

SNo	Specification	Qualitative Requirement (Q.R)			
1.	ADSL Interface	Support G.992.3 & 992.5 special Mask			
		Support latency path function			
		Support EOC & overhead channel Access			
		48 ports ADSL/ADSL 2+			
2.	Network Interface	e IEEE 802.30 100 base Tx			
		IEEE 802.3ab 1000 base T			
		IEEE 802.32 1000 base Lx/1000 base Sx			
3.	Bridge Function	VLAN tagging complies with IEEE 802.1Q			
		Support GVRP function			
		Provide 1024 configurable VLANs			
4.	Management	Local Management			
		Support SNMP V1.0 & V2 c			
		EMS Supporting			
5.	IP Network Interface	Support RFC 2684 Bridged mode			
		Support IGMP VZ			
		Support 256 Multi cast groups			
6.	Subscriber Management	Ethernet MAC filtering			
		64 K Mac address			
		Port isolation function			
7.	Power Supply	AC input 180 - 230v AC			
		DC input 36 - 72v DC			
	Power consumption	100 Watts			
8.	Weight	Upto 10 Kg			
9.	Operating Temp	0 to 50°C			
10 .	Storage Temperature	-30 to 70°C			

QUALITATIVE REQUIREMENTS: DSLAM 100 Subscribers

Pavitra Chakravarty,
DC (IT), CRPF

12 1.11

GC, ESG, NSG

K. Ramasubramanian,

Sr. T.D., NIC

Pardecp Yadav,

IG (Comn), CRPF

AC, ITBP

Mayank Kumar Dansena,

AC (IT), CRPF

Lt P. P. S. Manhas,

SC, ESG, NSG

Alok Roy Choudhary,

SSALMIC

Sonu Sikarwar,

AC, CISF

P/S. Virk,

DG (IT), BSF

Sanjeev Kumar,

AC, SSB

Amarjeet Singh,

E. ASSTT. DIR., DCPW

S. M. Hasnain,

DIG (IT), CRPF

[Approved / Not Approved]

Prakash Mishra, IPS

DG, CRPF

771 1- 61

TRIAL DIRECTIVE OF DSLAM 100 SUBSCRIBERS

All parameters/specifications mentioned in QRs will be checked by the Board of Officers by ascertaining/verifying following checks in the presence of Vendor/Supplier/Manufacturer. In case of any discrepancies/problem, the vendor/rep of firm will demonstrate the features to the Board of officer of the force concerned. Further, if proper testing instrument for testing these parameters is not available with customer, same will be arranged by the vendor.

- (a) **Physical Checks**. In this category, specifications of the equipment will be checked physically as per QRs.
- (b) **Functional Checks**. The vendors will show all the features/configuration of the equipment functioning on ground to the board of officers during trials.
- (c) <u>Submission of Certificates</u>. Specification which cannot be checked due to lack of testing facilities/expertise, self-certificate of OEM has to be provided by the vendor/bidder during trial.

SNo	Specification	Qualitative Requirements (QRs)	Trial Directive
1.	ADSL Interface	Support G.992.3 & 992.5 special Mask Support latency path function Support EOC & overhead channel Access	Board will carry out the functional test of the mentioned parameters. Also, the board will check the OEM compliance certificate submitted by the vendor. In case of any discrepancies/problem, the vendor/rep of
2.	Network Interface	48 ports ADSL/ADSL 2+ IEEE 802.30 100 base Tx IEEE 802.3ab 1000 base T	firm will demonstrate the features to the Board of officer. The board will carry out the physical check and functional test of the provided
		IEEE 802.32 1000 base Lx/1000 base Sx	specifications and also check the OEM certificate provided by the vendor. Further, in case of any discrepancies/ problem, the vendor/rep of firm will demonstrate the features to the Board of officer
3.	Bridge Function	VLAN tagging complies with IEEE 802.1Q Support GVRP function Provide 1024 configurable VLANs	Board will carry out the physical check as well as functional test of the mentioned parameters. Also, the board will check the OEM compliance certificate submitted by the vendor. In case of any discrepancies/problem, the vendor/rep of firm will demonstrate the features to the Board of officer.
4.	Management	Local Management Support SNMP V1.0 & V2 c EMS Supporting	The board will carry out the physical check and functional test of the provided specifications and also check the OEM certificate provided by the vendor. Further, in case of any discrepancies/ problem, the vendor/rep of firm will demonstrate the features to the Board of officer
5.	1P Network Interface	Support RFC 2684 Bridged mode Support IGMP VZ Support 256 Multi cast groups	The board will carry out functional test of the given specifications and also check the OEM certificate provided by the vendor.

12. I land

June June

My privet of

	Temperature		certification for the given feature.	
10.	Storage	-30 to 70°C	The vendor will provide the OEM	
	1		certification of the mentioned feature.	
9.	Operating Temp	0 to 50°C	The vendor will provide the OEM	
			the weight of the device.	
8.	Weight	Upto 10 Kg	The board will physically check and assess	
			Board of officer.	
			firm will demonstrate the features to the	
			discrepancies/problem, the vendor/rep of	
	•		the vendor. In case of any	
	consumption	·	OEM compliance certificate submitted by	
	Power	100 Watts	parameters. Also, the board will check the	
		DC input 36 - 72v DC	well as functional test of the mentioned	
7.	Power Supply	AC input 180 - 230v AC	Board will carry out the physical check as	
			Board of officer.	
			firm will demonstrate the features to the	
			discrepancies/problem, the vendor/rep of	
			the vendor. In case of any	
			OEM compliance certificate submitted by	
		Port isolation function	parameters. Also, the board will check the	
•	Management	64 K Mac address	well as functional test of the mentioned	
6.	Sscriber	Ethernet MAC filtering	Board will carry out the physical check as	
•				

Pavitra Chakravarty, DC (IT), CRPF

AC (IT), CRPF

Mavank Kumar Dansena.

Col. S. Balakrishanan, Lt. Cot. P. S. Manhas, GC, ESG, NSG SC, ESG, NSG

Alok koy Choudhary,

K. Ramasubramanian, Alok koy Choudha: Sr. T.D., NIC SSA, NIC

> Sonu Sikarwar, AC, CISF

Amarjeet Singh,

AC, SSB

P. S. Virk,

Sanjeev Kumar,

DC (IT), BSF

E. ASSTT. DIR., DCPW

S. M. Hasnain, DIG (IT), CRPF

Shailendra kayımar IG (Conn), CRPF

Pardeep Yadav,

AC, ITBP

[Approved / Not Approved]

Prakash Mishra, IPS
DG, CRPF