## F.No. P-63013/27/2013-Ord/BSF/MHA-Prov-I 9850 Bharat Sarkar/Government of India Griha Mantralaya/Ministry of Home Affairs **PM Division**

26. Man Singh Road, Jaisalmer House New Delhi, Dated 6 December, 2014

To.

DsG: AR (through LOAR), BSF, CISF, CRPF, ITBP, SSB, NSG & BPR&D.

QRs and Trial Directive for Clear water anywhere under the Subject: Sun/solar powered water filtration plants system/solar water filter 7 stage.

The QRs and Trial Directives in respect of Clear water anywhere under the Sun/solar powered water filtration plants system/solar water filter 7 stage as per Annexure have been accepted by the Competent Authority in MHA.

- The CAPFs concerned will be accountable for correctness of the QRs/Trial Directives.
- Henceforth, all the CAPFs should procure the above item required by them strictly as per the laid down Technical Specifications/QRs.

Yours faithfully,

Encl: As above

assiett. (P.K. Srivastava)

Under Secretary to the Govt of India

Tel: 23381278

Copy forwarded for necessary action to :-

The Section Officer (IT), MHA: It is requested to host the QRs and Trial Directives (soft copy attached) on the MHA website (under the page of Organizational Set up- Police Modernization Division- Qualitative Requirement under Miscellaneous Equipments.

Copy to: Director (Procurement), MHA.

Section Officer (Prov

Appendin. 1) (1) (155)

## DIRECTOR GENERAL BORDER SECURITY FORCE PROVISIONING DIRECTORATE (ORD SECTION)

The Sub-group of Technical Experts on Solar Water filtration system constituted by MHA vide their letter No. IV-24011/12/2011-Prov-I dated 13 Jun 2012, No. IV-24011/12/2011-Prov-I dated 28 Dec 2012 & UO No. IV-24011/12/2011-Prov-I- 350 dated 27 Jun 2013 held its meeting at BSF Headquarters on 30<sup>th</sup> Oct 2013, 26<sup>th</sup> Dec 2013, 05 Feb 2014, 17 Apr 2014 & 06 June 2014 to finalize the Qualitative Requirement of Clear Water anywhere under the Sun/ Solar Powered Water Filtration plants System/Solar Water Filter 7 Stage for ITBP/NSG & SSB respectively.

After detailed deliberations the referred Sub-group has finalized the QRs which are as under:-

## OUALITATIVE REQUIREMENT OF CLEAR WATER ANYWHERE UNDER THE SUN/ SOLAR POWERED WATER FILTERATION PLANTS-SYSTEM/SOLAR WATER FILTER 7 STAGE

SL NO	SPECIFICATIONS	
1	System should provide minimum 7000 liters of drinking water per day (24HR) from a water source at 5 to 10 meters. The wastage of water in filtering process should not be more than 1% with automatic backwash system. System operating temperature should be +2 to +50 degrees.	
2	Pump motor should have all safety features built-in:  a) Dry running protection	
	b) Over voltage and under voltage protection c) Over load protection d) Over temperature protection	
3	System should use minimum 7 steps to clean the water point by point:  a) Dirt debris b) fine particulates c) metallic compounds d) Organic particle e) Bacterial f) viral contamination	
	g) Arsenic compound, pesticide or toxic compounds	
4	No harmful or hazardous chemicals should be used in the filtration process	
5	All filter media and hardware are of EPA and NSF approved products and meet or surpass EPA or WHO standards for potable drinking water as per BIS standards IS 10500: 2012 or latest. The final out put of water from system must be in accordance with acceptable limit of BIS standards IS 10500: 2012 or latest.	
6	Simple backwash mechanism should help maintain optimal system operation when in field. (trial demonstration)	
7	Adsorption media in the system should clean highest level of arsenic (III & V), lead, cadmium, iron and heavy metal contamination in water.	
8	Adsorption media should last for 4 years or more before replacement. All filtration housing should be of stainless steel.	
9	The bacteriological filter cartridges used in the system should be easily cleaned in the field by pressure steam cleaning or cleaning with a chlorine solution.	
10	a) The system should have power back up from sealed maintenance free batteries or batteries of better technology of 12/24volt for minimum 4 hrs and charged by solar panel of 100 watt suitable	

All I

X VI

Smilin

10h, vo

ded.
ded.
eels
eels
eels in
ın k,
k,
be
be per
per
em
cts
cts m.
m. ſC
1C
}
7
İ
-
-
-
-
ļ
- 
R # ]
c1.
, c1.
, c <u>i</u> :
, cj.:
•
su O
•
•
•
•
•
•

BORDER SECURITY FORCE


Appendix - 13 (69)

## TRIAL DIRECTIVES OF CLEAR WATER ANYWHERE UNDER THE SUN/ SOLAR POWERED WATER FILTRATION PANTS-SYSTEM/ SOLAR WATER FILTER 7 STAGE.

WATER FILTRATION PANIS-SYSTEM/ SOLAR WATER FILTER / STAGE.				
QR Clean water anywhere under the sun / solar powered water filtration plants –system / solar water filter 7 stage	TRIAL DIRECTIVE			
1) System should provide minimum 7000 liters of drinking water per day (24HR) from a water source at 5 to 10 meters. The wastage of water in filtering process should not be more than 1% with automatic backwash system. System operating temperature should be +2 to +50 degrees.  2) Pump motor should have all safety features built-in:  a) Dry running protection  b) Over voltage and under voltage protection	<ol> <li>Connect the system to the water source at input pipe &amp; output pipe to a water tank (10,000L) and run the system for 24 hr with solar power and AC/DC power source when needed and collect 7000L in a clean tank with water wastage not more than 1%. (Tender company to provide the pipes &amp; storage tanks for trials)</li> <li>System should be able to pump water from within a minimum depth of 5 meters to a tank of capacity 10000 Ltr of underground tank / open source of water or direct water supply from water supply system.</li> <li>Drinking Water test to be conducted by Testing Lab having ISO 9001 certification and NABL accreditation to pass acceptable limits of BIS IS 10500 drinking water specification 2012 or latest. Water sample to be collected by the Testing Lab during the trials.</li> <li>OEM to certify the operating temp</li> <li>To be physically checked by the BOO and OEM to provide certificate in commensuration with QR no 2</li> </ol>			
c) Over load protection d) Over temperature protection	a) Perform the minimum 7 steps of water purification point by			
3) System should use minimum 7 steps to clean the water point by point :- a) Dirt debris b) fine particulates	point along with the testing of output water at each stage to showcase the effectiveness of each stage to clean the water from contamination as per QR no 3			
c) metallic compounds d) Organic particle e) Bacterial f) viral contamination g) Arsenic compound, pesticide or toxic	b) Lab test of water from each stage will be carried out by the BOO and final clean water output as per BIS latest standards			
compounds 4) No harmful or hazardous chemicals should be used in the filtration process	Certificate to be provided by the OEM filter media manufacturex.			
5) All filter media and hardware are of EPA and NSF approved products and meet or surpass EPA or WHO standards for potable drinking water as per BIS standards IS 10500: 2012 or latest. The final out put of water from system must be in accordance with acceptable limit of BIS standards IS 10500: 2012 or latest.	1) Filter media and Hardware Certifications from NSF International to be provided. BOO will physically check the certificate.  2) Water Test report from national or international accredited lab to be provided for the water test result to meet or surpass the US EPA or WHO standards by the OEM. BOO will physically check the certificate.  3) All water samples taken during the trials will have to meet or surpass the BIS latest standards for drinking water. BOO will physically check the certificate.			

6) Simple backwash mechanism should help After performing the point 1(1), Take the water sample maintain opti al system operation when in field. and demonstrate the Backwash mechanism to maintain (trial demonstration) system operation. BOO will physically check. 7) Adsorption media in the system should clean 1) OEM (Adsorption media) lab test certificate to be highest level of arsenic (III & V), lead, cadmium. provided. iron and heavy metal contamination in water. 2) OEM (Adsorption media) LAB test report of water output meeting or surpassing the US EPS arsenic standard of 10 parts per billion to be provided. BOO will physically check 8) Adsorption media should last for 4 years or 1) System supplier to certify for duration of adsorption media. more before replacement. All filtration housing BOO will physically check should be of stainless steel. 2) Physical inspection of system & supplier to certify the stainless steel. BOO will physically check 9) The bacteriological filter cartridges used in the 1) After running the system for 2 days, perform the live test system should be easily cleaned in the field by of cleaning with chlorine solution or steam. BOO will physically check pressure steam cleaning or cleaning with a 2) Take water sample after running the system for 1 Hr, chlorine solution. which should meet or surpass BIS standards. BOO will physically check 10. a) The system should have power back up 1) Physical check of 1 solar panel which fits inside robust structure of the system should be done with the rain/dust from sealed maintenance free batteries or batteries cover on the system of better technology of 12/24volt for minimum 4 2) System provider will demo the system runs on solar panel. hrs and charged by solar panel of 100 watt suitable then only with battery and last with direct AC or DC power to b) System should be able to run on regular AC/DC check system runs independently on either of the power 12/24 volt power source if needed. source. BOO will physically check c) system should be rain protected 3) System should be able to run for 24 hr with combination of battery power charged by solar panel and AC / DC power. BOO will physically check 4) OEM to provide certificate of the solar panel capacity (100) W) and measure the capacity during the trial and measure the capacity with a e-meter. BOO will physically check 11) Complete System should be housed in a robust 1) Physical dimension check to be done. structure of stainless steel with wheels less than 2) Weight checks to be done. 3) Ready the system on wheels and move the system. Load 35 (inch) L x 35 (inch) W x 45 (inch) H in the system to truck with ramp and unload, then test can be dimension and weight less than 160 kg (including done on train, aircraft (IL-76), helicopter M17, loading the structure) able to move for loading and and unloading. offloading on to truck, trolley, aircraft, train. 4) System provider to arrange for forklift to check design of System should be forklift ready. System will come the system, so that it is fork lift ready for loading and with extra spare tools kit including 2 spare UV unloading for truck, train, aircraft. BOO will physically filtration light and handheld torch check 5) Tool inspection to be done. 6) Physical check for spare 2 UV filtration light and handheld torch. 12) Operator level training and maintenance level QRs clause Srl No.12 to be incorporated in the tender training of minimum 15 days to be provided by OEM to user to independently maintain and operate the system as per company SOP for daily use. On site support should be provided within one week in case of breakdown. System control design should be user friendly and easy to operate.

	(63) C
13) Minimum 2 year warranty to be provided for	1) System provider will certify warranty.
the system . any manufacturing defects and	
Company to provide system support at site in case	Note: AMC details to be provided by the vendor
of breakdown of system. Bidder will support with	
10 year shelf life operational cycle after the	
warranty (AMC) and service contract after 2 year	
warranty.	
14) Optional items to be provided as per the user	Each user to mention their demand for extra accessories if
requirement at the time of tender:-	needed during the tender and BOO will check the system
a) Aircraft drop kit.	during the tender as per the requirement of the user force.
b) Extra well drop pipe.	
c) Collapsible water storage bladder tank	
(Pillow tanks)	
d) De- salination.	
15) Water testing kit to be provided which must	BOO to check the system if the submitted kit is able to check
be able to detect following parameters :	the following contamination in water:
a) Bacteria	a) bacteria
b) Lead	b) lead
c) Pesticides	c)pesticides d) nitrates
d) Nitrates	e) chlorine
e) Chlorine	f) Ph level
f) Ph level	g) water hardness
g) Water hardness	



APPROVED/ NOT APPROVED

(D. K PATHAK), IPS (318114

DIRECTOR GENERAL

BORDER SECURITY FORCE