



**DIRECTORATE GENERAL, CRPF**  
**EAST BLOCK-7, SECTOR-1, R.K PURAM, NEW DELHI-66**  
**e-mail: [digeqpt@crpf.gov.in](mailto:digeqpt@crpf.gov.in) Tele No. 011-26109038**



No. B.V-7-C/2025-26-C (SFR)-QR CELL

Dated, the 24 April'2026

**Subject: - REQUEST FOR COMMENTS OF STAKEHOLDERS /OEM/FIRMS ON DRAFT QRs & TDs OF "SINGLE FREQUENCY REPEATER (SFR)" REGARDING.**

The Draft QRs/TDs of "**Single Frequency Repeater (SFR)**" are attached as **Appendix 'A'**. The OEMs/Vendors are requested to forward information of the product, which they can offer and also forward correct specifications of their product against each parameter. Only complied or not complied remarks will not be accepted. The firms are also requested to furnish the following details: -

- Whether you are OEM/Vendor?
- If vendor, details of OEM required.
- Authorization certificate from OEM.

2. The required information/details may please be forwarded at the following addresses by 01 **May'2026**.

Communication Directorate, CRPF  
East Block-7, Sec-1, R.K. Puram, New Delhi-110066  
Email: [comncell@crpf.gov.in](mailto:comncell@crpf.gov.in)

3. An early response is requested.

(Megh Raj)  
**DIG (Equipment)**  
**Communication & IT Branch**  
**Directorate General, CRPF**

**DRAFT QRs/TDs OF SINGLE FREQUENCY REPEATER SET**

S. N	Parameters	Specification	Trial directives
1.	<b>General</b>		
	i) Frequency Range	136-174 MHz (For VHF) 410-470 MHz (For UHF) (Full Band)	BOO will check practically
	ii) Repeater Mode	Single frequency TDD	BOO will check practically
	iii) Channel Capacity	16	BOO will check practically
	iv) TDMA	2 Slot	BOO will check practically
	v) Channel Spacing	12.5 KHz/25 KHz or better (as per user requirement)	BOO will check practically
	vi) Frequency Stability	± 1 PPM or better	BOO will check practically and Firm will submit certificate of Govt. Lab/ILAC/NABL Accredited Lab.
	vii) Type of Emission	Digital: 7K60FXE, 7K60FXD, 7K60FXW	BOO will check practically and Firm will submit certificate of Govt. Lab/ILAC/NABL Accredited Lab.
	viii) Weight	Less than 10 Kg	BOO will check practically
	ix) Power Source	i) DC 12V/24V/48V ii) AC: 180V-260V	BOO will check practically
	x) Protection	i) Reverse polarity protection ii) Protection against high VSWR	BOO will check practically
	xi) EMI/EMC	As per ETSI EN 301 489-1 and ETSI 301 489-5  /TEC/SD/DD/EMC-221/05 /OCT-16 or equivalent.	Firm will submit certificate of Govt. Lab/ ILAC/NABL Accredited Lab.
	xii) Duty cycle	Should be 100 % duty cycle at full power in both AC and DC operation	OEM will submit certificate
2.	<b>Transmitter</b>		
	i) R.F Power output	50 Watt ±1dB for VHF and 40 Watt ±1dB for UHF	BOO will check practically
	ii) FM Hum /Noise	-40 dB or better	
	iii) Modulation Limiting	± 2.5 KHz @ 12.5 KHz	
	iv) Adjacent Chanel power	-60 dB or better	
	v) Audio Distortion	Less than 3%	
3.	<b>Receiver</b>		
	i) Sensitivity	Digital: 0.20µV at 5% BER or better	BOO will check practically and Firm will submit certificate of Govt. Lab/ILAC/NABL Accredited Lab.
	ii) Selectivity	60 dB or better.	
	iii) Inter Modulation	70 dB or better	
	vi) Audio Response	+1, -3 dB	
	v) Rated Audio Distortion	Less than 3%	
4.	<b>Environmental Specification</b>		
	i) Operating Temperature	-30°C to + 60 °C	Firm will submit certificate of Govt. Lab/ ILAC/NABL Accredited Lab.
	ii) Storage Temperature	-40°C to + 70 °C	

	iii) Humidity	Max. 90% @ +40°C non-condensing	
5	Networking	Ad-hoc networking without any IP backbone.	Firm will show networking and interfaces related function of repeater practically
6	Interfaces	Ethernet port RJ-45 to provide a) Remote monitoring and status check	
7	Features		
	i) Dual Channel Voice Transmit (Optional)	Should be Available and Capable to Communicate through Both Channel at Same Time	BOO will check practically
	ii) Location Report	Should be available	BOO will check practically
	iii) Visualized Network Management	Should be available	BOO will check practically
	iv) Node auto-connected Networking feature	Should be capable to connect up to 16 or more single frequency repeater in network in multiple topology. (without IP & Microwave link)	BOO will check practically
8.	<b>Accessories</b>		
	i) Battery cable & Mounting fixtures	Should be supplied with Repeater	BOO will check practically by connecting battery cable & mounting fixtures with repeater.
	ii) Antenna	6dB or high gain Omni Directional antenna with 45-meter RF (LDF 1/2"/RG-217 as per user requirement)	Firm will submit Certificate of Govt. Lab/ ILAC/NABL Accredited Lab
	iii) Programming kit	All necessary programming software and hardware required for the set will be provided. (As per user requirement)	BOO will check it practically that all necessary programming software and hardware are available as per user requirement.
	iv) Literature	i) User's manual with each radio sets should be provided free of cost in soft as well as hard copy. ii) Technical repairing manual with complete block diagram, circuit layout etc should be provided in soft as well as hard copy. (As per user requirement)	BOO will check it physically that User and Technical manual are available as per user requirement.