

मुख्यालय राष्ट्रीय सुरक्षा गारद
गृह मंत्रालय (भारत सरकार)
सम्भरण शाखा (आयुद्ध अनुभाग)
मेहरम नगर, पालम, नई दिल्ली-37

संख्या-पी/604/25/389/C Pistol/ई0-157502/संभरण(ऑर्डनेंस)/मु0रा0सु0गा0/ 432 दि0 20 अप्रैल 2026

विषय: 9x19 एम0एम0 कम्पाक्ट पिस्टल (9 x 19mm Compact Pistol) के अंतिम गुणात्मक आवश्यकता (क्यू.आर.) और परीक्षण निर्देशों (टी.डी.) का प्रेषण।

तकनीकी विशेषज्ञों के उप समूह द्वारा किए गये सूत्रीकरण एवम महानिदेशक, राष्ट्रीय सुरक्षा गारद द्वारा अनुमोदित 9x19 एम0एम0 कम्पाक्ट पिस्टल (9 x 19mm Compact Pistol) के अंतिम गुणात्मक आवश्यकता (क्यू.आर.) और परीक्षण निर्देशों (टी.डी.) को अग्रिम कार्यवाही हेतु प्रेषित किया जाता है।

संलग्न- उपरोक्तानुसार


(राजेश रंजन)

ग्रुप कमांडर (क्रय)

फोन- 011-25663100

ईमेल- gcproc@nsg.gov.in

वितरण :


1.	संयुक्त सचिव (पुलिस आधुनिकीकरण), गृह मंत्रालय, जेसलमेर हाउस, नई दिल्ली। ई0मेल: us-prov2@mha.gov.in	सूचनार्थ हेतु।
2.	वरिष्ठ तकनीकी निदेशक, एन0आई0सी0, गृह मंत्रालय, नार्थ ब्लॉक, नई दिल्ली। ई0मेल: soit@nic.in mpsugandhi@nic.in	आपसे अनुरोध है कि उपरोक्त क्यू0आर0/टी0डी0 को गृह मंत्रालय के वेबसाईट पर पुलिस आधुनिकीकरण डिविजन- क्यू0आर0- कैटगरी – Weaponry में ऑपलोड करने का कष्ट करें
3.	महानिरीक्षक/निदेशक (आर0एण्ड डी), बी0पी0आर0एण्ड डी0, महिपालपुर, नई दिल्ली। ई0मेल- igmod@bprd.nic.in/dd-mod@bprd.nic.in	
4.	अतिरिक्त महानिदेशक, पी0पी0 एण्ड टी0, रूम संख्या- 37, एच ब्लॉक, डी0जी0क्यू0ए0, भारत सरकार, रक्षा मंत्रालय, रक्षा उत्पादन विभाग, गुणवत्ता आश्वासन निदेशालय, नई दिल्ली। ई0मेल: saarmt-dgqa@gov.in	
5.	उप महानिरीक्षक (सम्भरण), के0रि0पु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल: digprov@crpf.gov.in/ dcord@crpf.gov.in	
6.	उप महानिरीक्षक (सम्भरण), सी0सु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprovfhq@bsf.gov.in / comdtord@bsf.nic.in	
7.	उप महानिरीक्षक (सम्भरण), के0ओ0सु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprov@cisf.gov.in, aigtech@cisf.gov.in	
8.	उप महानिरीक्षक (सम्भरण), भा0ति0सी0पु0, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprov@itbp.gov.in/digcommn@itbp.gov.in	
9.	उप महानिरीक्षक (सम्भरण), एस0एस0बी0, आर0के0पुरम0, नई दिल्ली। ई0मेल: digprov@ssbdel.in/ cr.ssbdel@nic.in	
10.	उप महानिरीक्षक (सम्भरण), असम राईफल, (एल0ओ0ए0आर0 द्वारा) ई0मेल : loar-mha@nic.in	
11.	ग्रुप कमांडर, ऑप्स (डब्लू0ई0), मु0रा0सु0 गारद - सूचनार्थ एवं आवश्यक कार्यवाही हेतु।	
12.	मुख्यालय, सी0टी0एफ0, रा0सु0 गारद - सूचनार्थ एवं आवश्यक कार्यवाही हेतु।	
13.	नोडल अधिकारी (जेम) - सूचनार्थ एवं आवश्यक कार्यवाही हेतु। ई0मेल:advisor-di@gem.gov.in	
14.	हिन्दी सेल, मु0 रा0सु0गा0 को इस आशय के साथ है कि उक्त क्यू0आर0/टी0डी0 का हिन्दी रूपान्तरण कर 03 दिन के अन्दर प्रस्तुत करने हेतु।	

QRs/TDs OF 9MM COMPACT PISTOL


Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
1.	Introduction.	Pistol is a short range semi-automatic compact weapon used for personal security to cover the target at short ranges.	
<u>OPERATIONAL PARAMETERS</u>			
2.	Caliber	9mm x 19mm	OEM to provide self certificate. BOO of physically check the caliber with calibrated gauge provided by the OEM. Validity of calibration certificate of gauge to be checked by BOO.
3.	Ammunition Type	9 mm x 19 mm (In service ammunition)	Tendering agency to specify in-service ammunition and make it available for trial testing on payment basis.
4.	Weight	Pistol without Magazine - Not more than 600g. Empty Magazine = Not more than 80g	To be physically checked by the BOO.
5.	Height with sight & Magazine fitted	Less than 116 mm	To be physically checked by the BOO.
6.	Length	Less than 168mm	To be physically checked by the BOO.
7.	Width	Less than 30mm	To be physically checked by the BOO.
8.	Firing Mode	Semi- Automatic.	To be physically checked by the BOO by firing the weapon at the range.
9.	Effective Range	Not less than 25 meters.	Five rounds of in- service ammunition provided by Tendering agency on payment basis will be fired from 25 meters manually and minimum four rounds should hit the Fig 11 target. To be physically checked by the BOO.



Ragul MR
Dy Comdt/ EXE, CISF



Prabhat Kumar Manna,
Insp (Armr), SSB



Amit Kumar,
Dy Comdt/ AIA, BSF



Bhompal,
Asstt Comdt/ Armr
ITBP



Narendra Kumar,
Asstt Comdt, CRPF



Nb Sub RK Singh,
Assam Rifles



Maj Amit
52 SAG, NSG



Lt Col Sumit Mahata,
SC (WE), HQ NSG



Sh. Jugraj Singh,
ADQA (SA), DGQA



Rajesh Ranjan
GC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
10.	Accuracy	When fired six rounds at range of 9 mtr, five out of six shots should be within a rectangle of 51mm horizontal x 76mm vertical.	<p>(i) After zeroing of weapon, six rounds of in- service ammunition provided by Tendering agency on payment basis will be fired from 9 mtr manually and minimum five rounds should hit within specified group size. To be physically checked by the BOO.</p> <p>(ii) OEM to provide firer and target. In case OEM requests for a firer from user agency, it is to be provided only after obtaining NOC to the effect that "OEM will not question/claim the skill of the firer and the result of trial firing will be acceptable to him"</p> <p>(iii) Maximum 15 rounds will be provided for zeroing.</p> <p>(iv) Maximum three attempts will be provided for accuracy test.</p>
11.	Reliability	<p>In a firing cycle of 600 rounds, the pistol should not suffer more than two Class-I, one Class-II and No Class-III stoppages, which are classified as follows:-</p> <p>(a) Class-I stoppage- Can be removed by the firer within 10 seconds without the use of any tools/Equipment/spares by using only immediate action drills.</p> <p>(b) Class -II stoppage – Can be removed by the firer in 10 seconds to 10 minutes using tools/Equipment /spares issued with the weapon.</p> <p>(c) Class – III stoppage – Takes more than 10 minutes or special tools/equipment to rectify defects and resume firing.</p>	<p>To be physically checked by the BOO.</p> <p>(i) Firing of 600 rounds will be done in six cycles of 100 rounds each, using two sample weapons of each firm.</p> <p>(ii) 100 rounds will be fired continuously within duration of 5 minutes.</p> <p>(iii) After firing 100 rounds, a gap of 5 minutes will be given for cooling of the weapon.</p> <p>(iv) No cleaning/maintenance are permitted during this test. This excludes actions done to remove stoppages.</p> <p>(v) Ammunition and firer will be provided by the respective OEM. In case OEM requests for a firer from user agency, it is to be provided only after obtaining NOC to the effect that " OEM will not question/claim the skill of the firer and the result of trial firing will be acceptable to him" Buyer/tendering agency to provide in service ammunition on payment basis.</p> <p>(vi) Time will be recorded by the BOO using stop watch.</p> <p>(vi) Misfire will not be considered as stoppage.</p>



Rajat MR
Dy Comdt/EXE, CISF



Ajay Sub RK Singh,
Assam Rifle



Prabhat Kumar Manna,
Insp (Armed), SSB



Major Amit
S2 SAG, NSG



Anil Kumar,
Dy Comdt/Armed, BSF

LT Col Sumit Mahala
S2 CWO, HQ NSG



Bhupat
AC/Armed, ITBP



Jugal Singh,
ADP/Armed, DGOA





Narendra Kumar
Asst Comdt, CRPF





Rajesh Ranjan
QC (Proc), 1st NSG


Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
12.	Inter changeability Test	Interchangeability test is conducted to ascertain the modularity of critical components of the weapon by replacement of sub assemblies. Pistol should be able to fire without any stoppages.	<p>Requirement of Stores</p> <p>Weapon : 02 Complete weapon Ammunition : 02 full magazines. Working table : 01 No. (size 6m x 1.5 m approx). Marker pen : 01 permanent silver coloured marker for marking on weapon and components.</p> <p>Procedure</p> <p>(a) Mark the selected weapons alongwith sub – assemblies & components as SI No 1 & SI No 2. (b) Dismantle & re-assemble the interchangeable components/sub-assemblies of the pistol. (c) Verify the serviceable of re-assembled weapons by applying gauges supplied by OEM and hand functioning (to check free movement moving parts & functionality of change lever at various designated mode). (d) Weapon will be undertaken for firing if above parameters confirm. (e) Fire seven rounds in single shot mode fire within 15 seconds.</p> <p>Observation</p> <p>(a) Interchanged weapons should pass the gauging parameters and hand functioning. (b) The weapons should not suffer from any class-II or class III stoppage. (c) Records all damages & stoppage, if any.</p> <p>All dynamic components which make the Pistol fire should be interchangeable. OEM to provide list of such components in their weapon which take part in dynamics of weapon and can be interchanged.</p>



Rajat NB
Dy Comd/ExC, CISF


Prabhakar Kanda Manda,
Insp (Arms), SSB



Amit Kumar,
Dy Comd/ATA, BSE



Bhupal,
Asst Comd/Arms
17 SD



Narendra Kumar
Asst Comd, CRPF


NB Sub RK Singh
Assem Rifle



Maj Amit
S2 SAG, NSG



Lt Col Sumit Mahala
SC (WB), HANSB



Jugraj Singh
ADDA (SAD), DGDA



Rajesh Ranjan
GC (Proc), HANSB


Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
13.	Adverse Condition Test	(a) Sand Test. (b) Water Test. (c) Drop Test.	(i) JSG 0131: 2021/ TOP 3-2-045 or equivalent procedure to be adopted for these tests. (ii) OEM to provide certificate from any international/ NABL accredited lab /NFSU/DRDO labs/DGQA/Govt lab. OEM to provide contact person details, phone number, address email address & website of the lab. Authenticity of certificate must be confirmed by the BOO. (iii) The certificate will remain valid for 05 years from the date of its issue. The testing of weapon (at any national level lab) for issue of fresh certificate /renewal after expiry of the validity period of certificate may be facilitated by writing a letter to concerned testing agency/ lab on request of firm, if required.
14.	<u>Environment Condition</u> (a) Operating Temperature. (b) Storage Temperature (c) Humanity Test	(a) -30 degree C to +50 degrees C. (b) -35 degrees C to +50 degrees C. (c) 95% RH at temp +40 degrees C.	(i) JSG 0131: 2021/ TOP 3-2-045 or equivalent procedure to be adopted for these tests. (ii) OEM to provide certificate from any NABL accredited lab/ NFSU/DRDO labs/DGQ/any Govt lab/ International accredited lab. OEM to provide contact person details, phone number, address, e-mail address & website of the lab. Authenticity of certificate must be confirmed by the BOO. (iii) The certificate will remain valid for 05 years from the date of its issue. The testing of weapon (at any national level lab) for issue of fresh certificate /renewal after expiry of the validity period of certificate may be facilitated by writing a letter to concerned testing agency/ lab on request of firm, if required.


Rajal MR
Dy Comdt, Exe. CIST
Atc
Maj Sub RK Singh
Assam Rifles


Poojhat Kumar Manora
Dy Comdt, SSB
Maj Amit
52 SAG, NSG


Jit Singh
Dy Comdt, AIA, BST
Lt Col Sunil Mahala,
SC (WE), ACO NSG


Shant
Blampal, Asst Comdt
ITBP
Jugraj Singh
4 DGQA (CSA), DGQA


Nalendra Kumar
Asst Comdt, CRPF
Rajesh Ranjan
GC (Pool), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
15.	Last Bullet Stop	The slide should lock in the open position after the last round is fired from the magazine.	To be physically checked by the BOO by loading the filled magazine and firing the weapon till magazine is empty.
16.	Color	Black/ Olive green to be specified by user at the time of tendering.	To be demonstrated by OEM & physically checked by BOO at the time of PDI.
PHYSICAL PARAMETERS			
17.	Indicator	Pistol should have loaded chamber indicator.	To be physically checked by BOO.
18.	Picatinny Rail	Mil standard 1913 Picatinny Rail integrated with the weapon on the lower side to provide interface for accessories like internationally available Tactical lights and LAD.	To be physically checked by BOO.
19.	Reflex Sight (Optional)	To be decided during tender	To be physically checked by the BOO.
20.	Magazine Capacity	Minimum 07 rounds.	To be physically checked by the BOO.
21.	Grip	Ergonomically designed for better grip and handling.	To be physically checked by the BOO.



Rajni Me
Dy Comd/Exec, CISF



NB Sub RK Singh
Assan Rifle



Prabhat Kumar Manna
Iosp (Amr), SSB



Maj Amit
S2 SAG, NSG



Anil Kumar
Dy Comd/Amr, BSF



Lt Col Sunil Mahala
SC (WB), HQ NSG



Bhonpal, Asst Comd
17 BP



Jagraj Singh
A DGM (SA), DADA



Narendra Kumar
Asst Comd, CRPF



Rajesh Ranjan
QC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
22.	Furniture	Should be made up of high strength polymers/composite/reinforced scratch proof plastic of high strength enabling environmental stability.	To be physically checked by the BOO.
23.	Holster (Optional – User to specify)	Holster should have secure and effective “Thumb Break” to ensure quick drawing of pistol. The pistol should go inside the holster with accessories such as additional magazine, sights and tactical lights if specified by user in tender documents.	To be demonstrated by OEM & Physically checked by the BOO.
MISCELLANEOUS PARAMETERS			
24.	Safety	Pistol should have external applied safety and internal mechanical safety.	OEM to provide self certificate. Safety parameter to be verified by BOO.
25.	Field Stripping	Pistol should be easily stripped without any tools or with minimum tools & all cleaning parts to be designed for field cleaning.	To be demonstrated by OEM & physically checked by BOO.
26.	Life Cycle	15 years for weapon & minimum 20,000 rounds for barrel life.	(i) OEM to provide certificate from any NABL /International/DGQA/NFSU/ Govt lab. (ii) OEM to provide contact person details, phone number, address, e-mail address & website of the lab. (iii) Authenticity of certificate must be confirmed by the BOO.



Ragul MR
Dy Comdt/Exec, CISF




Prabhat Kumar Manra
1 DSP (Arms), SSB



Amit Kumar
Dy Comdt/AIA, BSF



Bhupal, Dy Comdt
17 BP




Nataraja Kumar
Asst Comdt, CRPF



NB Sub BK Singh
Assam Rifles



Maj Anil
S2 SAC, NSG



Lt Col Sumit Mahal
SC (WB), HQ NSG





Jugal Singh
AD (BSA), DGQA



Rajesh Radian
GC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
27.	Warranty	Minimums two years	OEM to provide warranty certificate.
28.	Accessories (Requirement and quantity to be specified by user)	Manufacturer should provide accessories to include:- (a) Magazine- 3 (one with weapon plus two additional) (b) Field Cleaning kit (one with each pistol) (c) Standard weapon tool kit. (d) Measurement gauge (Go & No go). (e) Rigid/hard shell case for transit of weapon. (f) Maintenance manual in English. (g) Technical literature in English. (h) Training manuals & user hand book. (j) Manufactures recommended list of spares (MRLS) duly mentioning the prices. (k) Training slides, brochures, video films & CDs.	Individual accessories to be demonstrated by OEM & physically checked by the BOO. Ser No c, d and k, user to specify the qty and scale as per reqmt and not to be included with each weapon.
29.	Training	In situ training for one week on operation maintenance, fault finding and user level repairs to be impacted by OEM to user	OEM to provide certificate for the same.


Ragul MR
Dy Comdt/ EXE, CISF


Prabhat Kumar Manna,
Insp (Armr), SSB


Amit Kumar,
Dy Comdt/ AIA, BSF



Bhompal,
Asstt Comdt/ Armr
ITBP



Narendra Kumar,
Asstt Comdt, CRPF


Nb Sub RK Singh,
Assam Rifles


Maj Amit
52 SAG, NSG


Sh. Jugraj Singh,
ADQA (SA), DGQA


Lt-Col Sumit Mahata,
SC (WE), HQ NSG


Rajesh Ranjan
GC (Proc), HQ NSG


Rahul R Nair, IPS
DIG (Prov), NSG


Princee Rani, IPS
IG (Prov), NSG

Approved/ ~~Not Approved~~


(B Srinivasan) IPS
Director General, NSG