


मुख्यालय राष्ट्रीय सुरक्षा गारद
गृह मंत्रालय (भारत सरकार)
सम्भरण शाखा (आयुद्ध अनुभाग)
मेहरम नगर, पालम, नई दिल्ली-37

संख्या-पी/604/25/389/C Pistol/ई0-157502/संभरण(ऑर्डनेंस)/मु0रा0सु0गा0/ 1015 दि0 15 जुलाई 2026

विषय: 9x19 एम0एम0 कम्पाक्ट पिस्टल (9 x 19mm Compact Pistol) के संशोधित गुणात्मक आवश्यकता (क्यू.आर.) और परीक्षण निर्देशों (टी.डी.) का प्रेषण।

तकनीकी विशेषज्ञों के उप समूह द्वारा किए गये सूत्रीकरण एवम महनिदेशक, राष्ट्रीय सुरक्षा गारद द्वारा अनुमोदित 9x19 एम0एम0 कम्पाक्ट पिस्टल (9 x 19mm Compact Pistol) के संशोधित गुणात्मक आवश्यकता (क्यू.आर.) और परीक्षण निर्देशों (टी.डी.) को अग्रिम कार्यवाही हेतु प्रेषित किया जाता है।

संलग्न- उपरोक्तानुसार


(राजेश रंजन)
ग्रुप कमांडर (क्रय)
फोन- 011-25663100
ईमेल- gcproc@nsg.gov.in

वितरण :

1.	संयुक्त सचिव (पुलिस आधुनिकीकरण), गृह मंत्रालय, जेसलमेर हाउस, नई दिल्ली। ई0मेल: us-prov2@mha.gov.in	सूचनार्थ हेतु।
2.	अनुभाग अधिकारी (आई0टी0), एन0आई0सी0, गृह मंत्रालय, नार्थ ब्लॉक, नई दिल्ली। ई0मेल: soit@nic.in mpsugandhi@nic.in	आपसे अनुरोध है कि उपरोक्त क्यू0आर0/टी0डी0 को गृह मंत्रालय के वेबसाईट पर पुलिस आधुनिकीकरण डिविजन- क्यू0आर0- कैटगरी - Weaponry के क्रम संख्या-1 पर दिनांक 20 अप्रैल 2026 को दर्शाये जा रहे क्यू0आर0/टी0डी0 को मिटाते हुए संलग्न क्यू0आर0/टी0डी0 को गृह मंत्रालय के वेबसाईट पर ऑपलोड करने का कष्ट करें।
3.	महानिरीक्षक/निदेशक (आर0एण्ड डी), बी0पी0आर0एण्ड डी0, महिपालपुर, नई दिल्ली। ई0मेल- igmod@bprd.nic.in/dd-mod@bprd.nic.in	
4.	अतिरिक्त महनिदेशक, पी0पी0 एण्ड टी0, रूम संख्या- 37, एच ब्लॉक, डी0जी0क्यू0ए0, भारत सरकार, रक्षा मंत्रालय, रक्षा उत्पादन विभाग, गुणवत्ता आश्वासन निदेशालय, नई दिल्ली। ई0मेल: saarmt-dgqa@gov.in	
5.	उप महानिरीक्षक (सम्भरण), के0रि0पु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल: digprov@crpf.gov.in/ dcord@crpf.gov.in	
6.	उप महानिरीक्षक (सम्भरण), सी0सु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprovfhq@bsf.gov.in / comdtord@bsf.nic.in	
7.	उप महानिरीक्षक (सम्भरण), के0औ0सु0बल, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprov@cisf.gov.in/ aigtech@cisf.gov.in	
8.	उप महानिरीक्षक (सम्भरण), भा0ति0सी0पु0, केन्द्रीय कार्यालय परिसर, लोदी रोड, नई दिल्ली। ई0मेल : digprov@itbp.gov.in/digcommn@itbp.gov.in	
9.	उप महानिरीक्षक (सम्भरण), एस0एस0बी0, आर0के0पुरम0, नई दिल्ली। ई0मेल: digprov@ssbdel.in/ cr.ssbdel@nic.in	
10.	उप महानिरीक्षक (सम्भरण), असम राईफल, (एल0ओ0ए0आर0 द्वारा) ई0मेल : loar-mha@nic.in	
11.	ग्रुप कमांडर, ऑप्स (डब्लू0ई0), मु0रा0सु0 गारद - सूचनार्थ एवं आवश्यक कार्यवाही हेतु।	
12.	मुख्यालय, सी0टी0एफ0, रा0सु0 गारद - सूचनार्थ एवं आवश्यक कार्यवाही हेतु।	
13.	नोडल अधिकारी (जेम) - सूचनार्थ एवं आवश्यक कार्यवाही हेतु। ई0मेल:advisor-di@gem.gov.in	
14.	हिन्दी सेल, मु0 रा0सु0गा0 को इस आशय के साथ है कि उक्त क्यू0आर0/टी0डी0 का हिन्दी रूपान्तरण कर 03 दिन के अन्दर प्रस्तुत करने हेतु।	

REVISED QRs/TDs OF 9MM COMPACT PISTOL

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
1.	Introduction.	Pistol is a short range semi-automatic compact weapon used for personal security to cover the target at short ranges.	
<u>OPERATIONAL PARAMETERS</u>			
2.	Caliber	9mm x 19mm	OEM to provide self certificate. BOO of physically check the caliber with calibrated gauge provided by the OEM. Validity of calibration certificate of gauge to be checked by BOO.
3.	Ammunition Type	9 mm x 19 mm (In service ammunition)	Tendering agency to specify in-service ammunition and make it available for trial testing on payment basis.
4.	Weight	Pistol without Magazine - Not more than 600g. Empty Magazine = Not more than 80g	To be physically checked by the BOO.
5.	Height with sight & Magazine fitted	Not exceeding 125mm	To be physically checked by the BOO.
6.	Length	Not exceeding 170mm	To be physically checked by the BOO.
7.	Width	Not exceeding 33mm	To be physically checked by the BOO.
8.	Firing Mode	Semi- Automatic.	To be physically checked by the BOO by firing the weapon at the range.
9.	Effective Range	Not less than 25 meters.	Five rounds of in- service ammunition provided by Tendering agency on payment basis will be fired from 25 meters manually and minimum four rounds should hit the Fig 11 target. To be physically checked by the BOO.


Dharendra Verma,
Comdt (Ord), CRPF


Anand Prakash Verma, Dy
Comdt (Trg), BSF


Jagdish Harad,
AC/ Exe, CISF


Binay Kumar, AD,
BPR&D


Maj Rounak Mishra
52 SAG, NSG


Shishu Pal Singh,
Insp/ Armr, ITBP


Lt Col SK Mahata,
SC (WE), HQ NSG


Lt Col Bimal Singh,
Assam Rifles (Through VC)



Jugraj Singh,
ADQA (SA), DGQA


Lt Col KD Ghorpade
SC (Ord), HQ NSG


Rajesh Ranjan
GC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
10.	Accuracy	When fired six rounds at range of 9 mtr, five out of six shots should be within a rectangle of 51mm horizontal x 76mm vertical.	(i) After zeroing of weapon, six rounds of in- service ammunition provided by Tendering agency on payment basis will be fired from 9 mtr manually and minimum five rounds should hit within specified group size. To be physically checked by the BOO. (ii) OEM to provide firer and target. In case OEM requests for a firer from user agency, it is to be provided only after obtaining NOC to the effect that "OEM will not question/claim the skill of the firer and the result of trial firing will be acceptable to him" (iii) Maximum 15 rounds will be provided for zeroing. (iv) Maximum three attempts will be provided for accuracy test.
11.	Reliability	In a firing cycle of 600 rounds, the pistol should not suffer more than two Class-I, one Class-II and No Class-III stoppages, which are classified as follows:- (a) Class-I stoppage- Can be removed by the firer within 10 seconds without the use of any tools/Equipment/spares by using only immediate action drills. (b) Class -II stoppage – Can be removed by the firer in 10 seconds to 10 minutes using tools/Equipment /spares issued with the weapon. (c) Class – III stoppage – Takes more than 10 minutes or special tools/equipment to rectify defects and resume firing.	To be physically checked by the BOO. (i) Firing of 600 rounds will be done in six cycles of 100 rounds each, using two sample weapons of each firm. (ii) 100 rounds will be fired continuously within duration of 5 minutes. (iii) After firing 100 rounds, a gap of 5 minutes will be given for cooling of the weapon. (iv) No cleaning/maintenance are permitted during this test. This excludes actions done to remove stoppages. (v) Ammunition and firer will be provided by the respective OEM. In case OEM requests for a firer from user agency, it is to be provided only after obtaining NOC to the effect that " OEM will not question/claim the skill of the firer and the result of trial firing will be acceptable to him" Buyer/tendering agency to provide in service ammunition on payment basis. (vi) Time will be recorded by the BOO using stop watch. (vi) Misfire will not be considered as stoppage.



Dhyanendra Verma
Comdt (Ord), CRPF



Anand Prakash Verma
Dy Comdt (Trg), BSF



Jagdish Handa
AC/Exe, CISF



Binay Kumar, AD, BPRD


Maj Roubale Mishra
BSF, NSG



Subish Dal Singh, Insp/Arms
ITBD


Lt Col SK Mahata
SC(WB), H&MSG


Lt Col Bindal Singh
AR (Throug VC)



Jyotirmay Singh, AD (SA)
DGOA


Lt Col RD Ghorpade
SC (Ord), H&MSG


Rajesh Ranjan
GC (Proc), H&MSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
12.	Inter changeability Test	Interchangeability test is conducted to ascertain the modularity of critical components of the weapon by replacement of sub assemblies. Pistol should be able to fire without any stoppages.	Requirement of Stores Weapon : 02 Complete weapon Ammunition : 02 full magazines. Working table : 01 No. (size 6m x 1.5 m approx). Marker pen : 01 permanent silver coloured marker for marking on weapon and components. Procedure (a) Mark the selected weapons alongwith sub – assemblies & components as SI No 1 & SI No 2. (b) Dismantle & re-assemble the interchangeable components/sub-assemblies of the pistol. (c) Verify the serviceable of re-assembled weapons by applying gauges supplied by OEM and hand functioning (to check free movement moving parts & functionality of change lever at various designated mode). (d) Weapon will be undertaken for firing if above parameters confirm. (e) Fire seven rounds in single shot mode fire within 15 seconds. Observation (a) Interchanged weapons should pass the gauging parameters and hand functioning. (b) The weapons should not suffer from any class-II or class III stoppage. (c) Records all damages & stoppage, if any. All dynamic components which make the Pistol fire should be interchangeable. OEM to provide list of such components in their weapon which take part in dynamics of weapon and can be interchanged.


Dhirendra Verna.
Condt (Ord), CRPF



Anand Prakash Verma.
Dy Condt (Trg), BSF


Jagdish Harod.
AC Exe, CISF


Birendra Kumar, AD
BPRD


Maj Rakesh Mishra
S2 SAC, NSG



Shishu Pal Singh
Insp/Inm, ITBP


Lt Col SRC Mahata
SC (WE), HQ NSG


Lt Col Bimal Singh
AR (Through VC)



Anuraj Singh
ADQA (G), ISQA


Lt Col KD Ghosh
SC (Ord), HQ NSG


Rajesh Ranjan
GC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
13.	Adverse Condition Test	(a) Sand Test. (b) Water Test. (c) Drop Test.	(i) JSG 0131: 2021/ TOP 3-2-045 or equivalent procedure to be adopted for these tests. (ii) OEM to provide certificate from any international/ NABL accredited lab /NFSU/DRDO labs/DGQA/Govt lab. OEM to provide contact person details, phone number, address email address & website of the lab. Authenticity of certificate must be confirmed by the BOO. (iii) The certificate will remain valid for 05 years from the date of its issue. The testing of weapon (at any national level lab) for issue of fresh certificate /renewal after expiry of the validity period of certificate may be facilitated by writing a letter to concerned testing agency/ lab on request of firm, if required.
14.	<u>Environment Condition</u> (a) Operating Temperature. (b) Storage Temperature (c) Humanity Test	(a) -30 degree C to +50 degrees C. (b) -35 degrees C to +50 degrees C. (c) 95% RH at temp +40 degrees C.	(i) JSG 0131: 2021/ TOP 3-2-045 or equivalent procedure to be adopted for these tests. (ii) OEM to provide certificate from any NABL accredited lab/ NFSU/DRDO labs/DGQ/any Govt lab/ International accredited lab. OEM to provide contact person details, phone number, address, e-mail address & website of the lab. Authenticity of certificate must be confirmed by the BOO. (iii) The certificate will remain valid for 05 years from the date of its issue. The testing of weapon (at any national level lab) for issue of fresh certificate /renewal after expiry of the validity period of certificate may be facilitated by writing a letter to concerned testing agency/ lab on request of firm, if required.


 Dhirendra Verma
 Condt (Ord), CRPF


 Anand Prakash Verma
 Dy Condt (Trg), BSF



 Jagdish Harad
 AC/Exe, CISF


 Birendra Kumar, AO
 DRDO


 Maj Ramesh Mishra
 S2 SAG, NSG



 Shishu Pal Singh
 Insp/Arms, ITBP


 Lt Col S.C. Mahata,
 SC (W &), HQ NSG


 Lt Col Bimal Singh
 AR (Through VC)



 Jugraj Singh
 ADPA (SA), DGQA


 Lt Col KD Shorpane
 SC (Ord), HQ NSG


 Rajesh Ranjan
 Gc (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
15.	Last Bullet Stop	The slide should lock in the open position after the last round is fired from the magazine.	To be physically checked by the BOO by loading the filled magazine and firing the weapon till magazine is empty.
16.	Color	Black/ Olive green to be specified by user at the time of tendering.	To be demonstrated by OEM & physically checked by BOO at the time of PDI.
PHYSICAL PARAMETERS			
17.	Indicator	Pistol should have loaded chamber indicator.	To be physically checked by BOO.
18.	Picatinny Rail	Mil standard 1913 Picatinny Rail integrated with the weapon on the lower side to provide interface for accessories like internationally available Tactical lights and LAD.	To be physically checked by BOO.
19.	Reflex Sight (Optional)	To be decided during tender	To be physically checked by the BOO.
20.	Magazine Capacity	Minimum 07 rounds.	To be physically checked by the BOO.
21.	Grip	Ergonomically designed for better grip and handling.	To be physically checked by the BOO.


Dhirendra Verma
Condt (Com), CRPF


Shishu Pal Singh,
10sp/Arms, 11RP


Anand Prakash Verma
Dy Condt (Crg), BSF


Lt Col SK Malakia
SC (WE), HIO NSG


Jagdish Harod
AC/ Exe, CISF



Lt Col Bimal Singh
AR (Through vs)


Tejraj Singh,
ADDA (SA), DGQA


Binay Kumar, AD
BPR&D


Lt Col KD Shropade
SC (Com), HIO NSG


Maj Roudak Mishra
S2 SA9, NSG


Rajesh Ranjan
GC (prol), HIO NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
22.	Furniture	Should be made up of high strength polymers/composite/reinforced scratch proof plastic of high strength enabling environmental stability.	To be physically checked by the BOO.
23.	Holster (Optional – User to specify)	Holster should have secure and effective “Thumb Break” to ensure quick drawing of pistol. The pistol should go inside the holster with accessories such as additional magazine, sights and tactical lights if specified by user in tender documents.	To be demonstrated by OEM & Physically checked by the BOO.

MISCELLANEOUS PARAMETERS

24.	Safety	Pistol should have external applied safety and internal mechanical safety.	OEM to provide self certificate. Safety parameter to be verified by BOO.
25.	Field Stripping	Pistol should be easily stripped without any tools or with minimum tools & all cleaning parts to be designed for field cleaning.	To be demonstrated by OEM & physically checked by BOO.
26.	Life Cycle	15 years for weapon & minimum 20,000 rounds for barrel life.	(i) OEM to provide certificate from any NABL /International/DGQA/NFSU/ Govt lab. (ii) OEM to provide contact person details, phone number, address, e-mail address & website of the lab. (iii) Authenticity of certificate must be confirmed by the BOO.



Dharendra Verma,
Condt (Ord), CDPF


Anand Prakash Verma,
Dy Condt (Imp), BSF


Jagdish Harad
Hd Exc, CISF


Bisay Kumar, AD
BPPSD


Maj Randeep Mishra
S24A, NSG


Shishu Pal Singh
Iosp/Amor, ITBP


Lt Col SK Mahanta,
SC CWC, HQ NSG


Lt Col Binod Singh
AR (Brought VC)



Jugraj Singh,
ADDA (SA), DGOA


Lt Col KD Ghoshade
SC (Ord), HQ NSG



Rajesh Ranjan
SC (Proc), HQ NSG

Ser No	Parameter	Specifications (QRs)	Trial Directives (TDs)
27.	Warranty	Minimums two years	OEM to provide warranty certificate.
28.	Accessories (Requirement and quantity to be specified by user)	Manufacturer should provide accessories to include:- (a) Magazine- 3 (one with weapon plus two additional) (b) Field Cleaning kit (one with each pistol) (c) Standard weapon tool kit. (d) Measurement gauge (Go & No go). (e) Rigid/hard shell case for transit of weapon. (f) Maintenance manual in English. (g) Technical literature in English. (h) Training manuals & user hand book. (j) Manufactures recommended list of spares (MRLS) duly mentioning the prices. (k) Training slides, brochures, video films & CDs.	Individual accessories to be demonstrated by OEM & physically checked by the BOO. Ser No c, d and k, user to specify the qty and scale as per reqmt and not to be included with each weapon.
29.	Training	In situ training for one week on operation maintenance, fault finding and user level repairs to be impacted by OEM to user	OEM to provide certificate for the same.



Dharendra Verma,
Comdt (Ord), CRPF


Anand Prakash Verma, Dy
Comdt (Trg), BSF


Jagdish Harod,
AC/ Exe, CISF


Binay Kumar, AD,
BPR&D


Maj Rounak Mishra
52 SAG, NSG


Shishu Pal Singh,
Insp/ Armr, ITBP


Lt Col SK Mahata,
SC (WE), HQ NSG

Lt Col Bimal Singh,
Assam Rifles (Through VC)


Jugraj Singh,
ADQA (SA), DGQA


Lt Col KD Ghorpade
SC (Ord), HQ NSG


Rajesh Ranjan
GC (Proc), HQ NSG


Rahul R Nair, IPS
DIG (Prov), HQ NSG


Amit Pathak, IPS
IG (Prov), HQ NSG

Approved / ~~Not Approved~~


(B Srinivasan) IPS
Director General, NSG